

### PATH TO THE FUTURE



Picture and logos

### SELLING POINTS

- Panel VA rápido - Proporciona un tiempo de respuesta de 0,5 ms (GtG, mínimo), optimizando los colores y el brillo de la pantalla.
- Tasa de refresco de 200 Hz - Responde más rápido con fotogramas más fluidos.
- Tiempo de respuesta de 0,5 ms (GtG, mínimo) - Elimina el desgarro de pantalla y los fotogramas entrecortados.
- AI Vision - La nueva tecnología AI Vision no solo revela detalles en áreas oscuras, sino que también mejora el brillo general y satura los colores.
- Reducción de la luz azul - Utiliza una solución de software para reducir la emisión de luz en la región azul-violeta del espectro de luz azul.



1. 5-Way Navi Key
2. DC-in
3. 2x HDMI™ 2.0b (FHD@200Hz)
4. DisplayPort 1.4a (HBR3)
5. Headphone-out
6. Kensington Lock

**SPECIFICATION**

Modelo	SKU Number	9S6-3CF51T-010
	Entity MKT Name	MAG 274CF E20
	Part No	9S6-3CF51T-010
	Color	ID1/Black-Black
Pantalla	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312 (V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	AMD FreeSync™ Premium
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	3500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	53.088~221.2 KHz(H) / 48~200 Hz(V)
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	103%/85%
	NTSC (CIE1931 area percentage/overlap)	86%/80%
	sRGB (CIE1976 area percentage/overlap)	118%/99%
	sRGB (CIE1931 area percentage/overlap)	122%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	101%/91%
	Adobe RGB (CIE1931 area percentage/overlap)	90%/84%
	DCI-P3 (CIE1976 area percentage/overlap)	94%/94%
	DCI-P3 (CIE1931 area percentage/overlap)	90%/89%
	Rec.709 (CIE1976 area percentage/overlap)	118%/99%
	Rec.709 (CIE1931 area percentage/overlap)	122%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	68%/68%
	Rec.2020 (CIE1931 area percentage/overlap)	64%/64%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
Puertos E/S	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantía	Warranty	36M
Alimentación	Power Type	External Adaptor 19V 2.5A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	SDR : 21 HDR : 30
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) G (HDR)
	Power Cord Type	C13

Acesorios	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Diseño	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Tamaño y peso (producto)	Product Dimension with Stand (WxDxH) (mm)	613.5 x 249.8 x 438.3
	Product Dimension without Stand (WxDxH) (mm)	613.5 x 76.6 x 363.6
	Stand Dimension (WxDxH) (mm)	339.9 x 249.8 x 139.7
	Weight (Net kg)	3.34
	Weight Without Stand (kg)	2.95
Tamaño y peso (caja)	Inside Carton Dimension (WxDxH) (cm)	68.4 x 15.6 x 43.9
	Outer Carton Dimension (WxDxH) (cm)	69.9 x 17.1 x 46.2
	Weight (Gross kg)	5.5
Información sobre el código de barras	EAN	4711377391542