

## PATH TO THE FUTURE

Introducing the MSI MAG 274CXF esports gaming monitor. This cutting-edge monitor features a 27-inch FHD display with a lightning-fast 280Hz refresh rate and a rapid 0.5ms (GtG, Min.) response time. With the MAG 274CXF, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

## SELLING POINTS

- Panel Rapid IPS – Proporciona un tiempo de respuesta de 0,5 ms (GtG, mínimo), optimiza los colores y el brillo de la pantalla.
- Tasa de refresco de 240 Hz – Responde más rápido con imágenes más fluidas.
- Tiempo de respuesta de 0,5 ms (GtG, mínimo) – Elimina el tearing de imagen y los fotogramas entrecortados.
- AI Vision – La nueva tecnología AI Vision no solo revela detalles en áreas oscuras, sino que también mejora el brillo general y satura los colores.
- Reducción de la luz azul – Utiliza una solución de software para reducir la emisión de luz en la región azul-violeta del espectro de luz azul.



1. 5-way Joystick Navigator
2. AC-in
3. 2 x HDMI™ 2.0b (WQHD@144Hz)
4. Display Port 1.4a
5. Headphone out
6. AC-in
7. Kensington Lock



MONITORES

MAG 274QF X24

MAG 274QF X24

## SPECIFICATION

|              |                                             |                                  |
|--------------|---------------------------------------------|----------------------------------|
| Modelo       | Part No                                     | 9S6-3CE41H-051                   |
|              | Color                                       | ID1/Black-Black                  |
| Pantalla     | Screen Size                                 | 27" (68.58 cm)                   |
|              | Active Display Area (mm)                    | 596.736(H) x 335.664(V)          |
|              | Curvature                                   | Flat                             |
|              | Panel Type                                  | Rapid IPS                        |
|              | Resolution                                  | 2560x1440 (WQHD)                 |
|              | Pixel pitch (mm)                            | 0.2331(H)x0.2331(V)              |
|              | Aspect Ratio                                | 16:9                             |
|              | Dynamic Refresh Rate technology             | FreeSync Premium                 |
|              | Dynamic Refresh Rate Activated Range        | 48~240Hz                         |
|              | HDR (High dynamic range)                    | HDR Ready                        |
|              | SDR Brightness (nits)                       | 250                              |
|              | Contrast Ratio                              | 1000:1                           |
|              | DCR (Dynamic Contrast Ratio)                | 100000000:1                      |
|              | Signal Frequency                            | 128.67~175 KHz(H) / 48~240 Hz(V) |
|              | Refresh Rate                                | 240HZ                            |
|              | Response Time (MPRT)                        | 1ms(MPRT)                        |
|              | Response Time (GTG)                         | 0.5ms (Min.)                     |
|              | View Angles                                 | 178°(H)/178°(V)                  |
|              | NTSC (CIE1976 area percentage/overlap)      | 113%/88%                         |
|              | NTSC (CIE1931 area percentage/overlap)      | 89%/80%                          |
|              | sRGB (CIE1976 area percentage/overlap)      | 130%/99%                         |
|              | sRGB (CIE1931 area percentage/overlap)      | 126%/99%                         |
|              | Adobe RGB (CIE1976 area percentage/overlap) | 111%/93%                         |
|              | Adobe RGB (CIE1931 area percentage/overlap) | 93%/85%                          |
|              | DCI-P3 (CIE1976 area percentage/overlap)    | 103%/96%                         |
|              | DCI-P3 (CIE1931 area percentage/overlap)    | 93%/90%                          |
|              | Rec.709 (CIE1976 area percentage/overlap)   | 130%/99%                         |
|              | Rec.709 (CIE1931 area percentage/overlap)   | 126%/99%                         |
|              | Rec.2020 (CIE1976 area percentage/overlap)  | 75%/75%                          |
|              | Rec.2020 (CIE1931 area percentage/overlap)  | 66%/66%                          |
|              | Surface Treatment                           | Anti-glare                       |
|              | Display Colors                              | 1.07B                            |
|              | Color bit                                   | 10 bits (8 bits + FRC)           |
| Puertos E/S  | Headphone-out                               | 1                                |
|              | Card reader                                 | N/A                              |
|              | Lock type                                   | Kensington Lock                  |
|              | HDMI                                        | 2                                |
|              | HDMI version                                | 2.0b                             |
|              | HDMI HDCP version                           | 2.3                              |
|              | DisplayPort                                 | 1                                |
|              | DisplayPort version                         | 1.4a (HBR3)                      |
|              | DisplayPort HDCP version                    | 2.3                              |
| Garantía     | Warranty                                    | 36M                              |
| Alimentación | Power Type                                  | Internal Power Board             |
|              | Power Input                                 | 100~240V, 50/60Hz                |
|              | On-mode Power Consumption (KWh/1000h)       | 26                               |
|              | Annual Energy Consumption (KWh)             | 26                               |
|              | Standby-mode Power Consumption (W)          | 0.5                              |
|              | Off-mode Power Consumption (W)              | 0.3                              |
|              | Energy Efficiency Rating                    | F                                |
|              | Power Cord Type                             | C13                              |



MONITORES

MAG 274QF X24

MAG 274QF X24

|                                       |                                              |                       |
|---------------------------------------|----------------------------------------------|-----------------------|
| Accesorios                            | DisplayPort Cable                            | 1                     |
|                                       | HDMI Cable                                   | 0                     |
|                                       | DVI Cable                                    | 0                     |
|                                       | USB Type A to Type B Cable                   | 0                     |
|                                       | USB Type C to Type A Cable                   | 0                     |
|                                       | USB Type C to Type C Cable                   | 0                     |
|                                       | Thunderbolt Cable                            | 0                     |
|                                       | VGA Cable                                    | 0                     |
|                                       | 3.5mm audio Cable                            | 0                     |
|                                       | 3.5mm combo audio Cable                      | 0                     |
|                                       | 3.5mm Mic Cable                              | 0                     |
|                                       | Power Cord                                   | 1                     |
|                                       | AC Adaptor                                   | 0                     |
|                                       | Quick Guide                                  | 1                     |
|                                       | Warranty Card                                | 0                     |
|                                       | Mouse Bungee Unit                            | 0                     |
| Diseño                                | Adjustment (Tilt)                            | -5° ~ 20°             |
|                                       | VESA Mounting                                | 100x100mm             |
| Tamaño y peso (producto)              | Product Dimension with Stand (WxDxH) (mm)    | 613.5 x 249.7 x 438.5 |
|                                       | Product Dimension without Stand (WxDxH) (mm) | 613.5 x 62.1 x 362.5  |
|                                       | Stand Dimension (WxDxH) (mm)                 | 340 x 250 x 143       |
|                                       | Weight (Net kg)                              | 4.7                   |
|                                       | Weight Without Stand (kg)                    | 4.2                   |
| Tamaño y peso (caja)                  | Inside Carton Dimension (WxDxH) (cm)         | 68.3 x 12.7 x 44.8    |
|                                       | Outer Carton Dimension (WxDxH) (cm)          | 69.8 x 14 x 46.7      |
|                                       | Weight (Gross kg)                            | 6.55                  |
| Información sobre el código de barras | EAN                                          | 4711377281621         |