

PATH TO THE FUTURE

Introducing the MSI MAG 275QF E20 esports gaming monitor. This cutting-edge monitor features a 27-inch WQHD display with a lightning-fast 200Hz refresh rate and a rapid 0.5ms (GtG, Min.) response time. With the MAG 275QF E20, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

SELLING POINTS

- Panel IPS rápido: proporciona un tiempo de respuesta de 0,5 ms (GtG, mín.), optimiza los colores y el brillo de la pantalla.
- Tasa de refresco de 200 Hz: responde más rápido con fotogramas más fluidos.
- Tiempo de respuesta de 0,5 ms (GtG, mín.): elimina el tearing de la pantalla y las frecuencias de fotogramas entrecortadas.
- AI Vision: la nueva tecnología AI Vision no solo revela los detalles en las zonas oscuras, sino que también mejora el brillo general y satura los colores.
- Reducción de la luz azul: utiliza una solución de software para reducir la emisión de luz en la región azul-violeta del espectro de luz azul.



1. 5-way Joystick Navigator
2. AC-in
3. 2 x HDMI™ 2.0b (WQHD@144Hz)
4. Display Port 1.4a(HBR3)
5. Headphone out
6. Kensington Lock

SPECIFICATION

Modelo	Part No	9S6-3CAA1M-003
	Color	ID1/Black-Black
Pantalla	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) × 335.664(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	NVIDIA G-SYNC Compatible / AMD FreeSync™ Premium
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1200:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	130.56~544 KHz(H) / 48~200 Hz(V)
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/79%
	NTSC (CIE1931 area percentage/overlap)	83%/74%
	sRGB (CIE1976 area percentage/overlap)	115%/95%
	sRGB (CIE1931 area percentage/overlap)	115%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	100%/82%
	Adobe RGB (CIE1931 area percentage/overlap)	85%/76%
	DCI-P3 (CIE1976 area percentage/overlap)	93%/90%
	DCI-P3 (CIE1931 area percentage/overlap)	85%/84%
	Rec.709 (CIE1976 area percentage/overlap)	115%/95%
	Rec.709 (CIE1931 area percentage/overlap)	115%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	65%/65%
	Rec.2020 (CIE1931 area percentage/overlap)	60%/60%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Puertos E/S	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR3)
	DisplayPort HDCP version	2.3
Garantía	Warranty	36M
Alimentación	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	38
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C13	

Acesorios	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Diseño	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Tamaño y peso (producto)	Product Dimension with Stand (WxDxH) (mm)	613.3 x 220.1 x 454.6
	Product Dimension without Stand (WxDxH) (mm)	613.3 x 57.9 x 360.7
	Stand Dimension (WxDxH) (mm)	318.0 x 220.1 x 138.3
	Weight (Net kg)	3.95
	Weight Without Stand (kg)	3.57
Tamaño y peso (caja)	Inside Carton Dimension (WxDxH) (cm)	68.4 x 12.9 x 45.6
	Outer Carton Dimension (WxDxH) (cm)	70.4 x 14.9 x 48.6
	Weight (Gross kg)	6.24
Información sobre el código de barras	EAN	4711377386302