

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- PerfectEdge: el diseño con bisel fino en los cuatro lados te permite sumergirte por completo en una configuración multipantalla
- Disfruta de un entretenimiento de alta calidad con una tasa de refresco de 144 Hz más fluida y AMD FreeSync™.
- La pantalla con certificación TÜV garantiza la protección y la salud de tu vista.
- La tecnología MSI EyesErgo, con tecnología Anti-Flicker, ayuda a prevenir la tensión y la fatiga ocular.
- MSI Eye-Q Check te ayuda a realizar una autoevaluación de la vista y te recuerda que debes descansar cuando llevas mucho tiempo usando el monitor.
- El diseño compatible con montaje VESA te permite tener una configuración ordenada, lo que mejora tu comodidad y organización.
- MSI Power Link te permite encender tu ordenador de sobremesa MSI con solo pulsar el botón de encendido del monitor.
- Disfruta de versatilidad con distintos dispositivos gracias a las múltiples fuentes de entrada, como los puertos HDMI™ y Type-C.
- Compatible con el estándar de montaje VESA y diseño con ranura para accesorios.
- Dos altavoces integrados.



1. 5-Way Navi Key
2. DC-in
3. 1x HDMI™ 2.0 (FHD@144Hz)
4. 1x Type-C (DP alt.) w/ 15W PD
5. 1x Headphone-out
6. Kensington Lock

SPECIFICATION

Modelo	Part No	9S6-3PE7CM-002
	Color	ID1/Black-Black
Pantalla	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04(H) x 296.46(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	TBD
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	TBD/TBD
	NTSC (CIE1931 area percentage/overlap)	TBD/TBD
	sRGB (CIE1976 area percentage/overlap)	TBD/TBD
	sRGB (CIE1931 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1976 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1931 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1976 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1931 area percentage/overlap)	TBD/TBD
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Puertos E/S	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	1
	HDMI version	2.0
	HDMI HDCP version	2.3
Garantía	Warranty	24M
Alimentación	Power Type	External Adaptor 12V 4A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
	Power Cord Type	C13



BUSINESS PRODUCTIVITY MONITOR

PRO MP242 E14C

PRO MP242 E14C

Accesorios	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	1
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Diseño	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Tamaño y peso (producto)	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Tamaño y peso (caja)	Inside Carton Dimension (WxDxH) (cm)	60 x 12.5 x 40
	Outer Carton Dimension (WxDxH) (cm)	61.8 x 14.3 x 43
	Weight (Gross kg)	N/A
Información sobre el código de barras	EAN	4711377361217