



BUSINESS PRODUCTIVITY MONITOR
PRO MP242C
PRO MP242C

Be Your Window To The World



Picture and logos

SELLING POINTS

- La curvatura 1500R ofrece la experiencia visual más envolvente para trabajar y divertirse.
- La pantalla con certificación TÜV protege su vista y mantiene tu vista sana
- Las tecnologías Antiflicker y reducción de la luz azul evitan que tus ojos se cansen
- Software ergonómico, Display Kit, proporciona la herramienta más conveniente, el color y el modo de visualización adecuados mientras trabajas con él todos los días
- La tasa de refresco de 75 Hz proporciona una mejor experiencia de visualización
- Mantén la flexibilidad para tus diferentes dispositivos con múltiples fuentes de entrada: puertos HDMI y D-Sub (VGA)
- Diseño de montaje estándar VESA
- Te permite unirme en cualquier momento a una videollamada con los altavoces integrados



1. 1x DC Jack
2. 1x HDMI (1.4)
3. 1x D-Sub (VGA)
4. 1x Line-in
5. 1x Headphone-out
6. 1x Kensington Lock
7. 1x 5-Way Navigator + OSD Button



SPECIFICATION

Display	Screen Size	23.6" (60cm)
	Active Display Area (mm)	521(H) x 293(V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.8~90 KHz(H) / 48~75 Hz(V)
	Refresh Rate	75Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (Tr + Tf)	27ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	85%/75%
	NTSC (CIE1931 area percentage/overlap)	72%/70%
	sRGB (CIE1976 area percentage/overlap)	98%/95%
	sRGB (CIE1931 area percentage/overlap)	99%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	83%/82%
	Adobe RGB (CIE1931 area percentage/overlap)	75%/73%
	DCI-P3 (CIE1976 area percentage/overlap)	77%/77%
	DCI-P3 (CIE1931 area percentage/overlap)	74%/74%
	Rec.709 (CIE1976 area percentage/overlap)	98%/95%
	Rec.709 (CIE1931 area percentage/overlap)	99%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	56%/56%
	Rec.2020 (CIE1931 area percentage/overlap)	52%/52%
	Display Colors	16.7M
	Color bit	8 bits
	Note_HDMI™	1920 x 1080 (Up to 75Hz)
	Note_DVI	N/A
I/O Ports	Line-in	1
	HDMI™ version	1.4b
	HDMI™ HDCP version	1.4
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2
Onboard Graphics	HDMI™	1
	VGA	1
Power	Power Supply Type	External Adaptor 12V 2.5A
	Power Input	100~240V, 50/60Hz
	Power Cord Type	C13
In The Box	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	1
	AC Adaptor	1
	Warranty Card	0
	Quick Guide	1



PRO MP242C

PRO MP242C

Design	Adjustment (Tilt)	-7° ~ 22°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	615 x 155 x 425
	Outer Carton Dimension (WxDxH) (inch)	24.21 x 6.1 x 16.73
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	539.8 x 203 x 414.1
	Product Dimension with Stand (WxDxH) (inch)	21.25 x 7.99 x 16.3
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	539.8 x 321.8 x 74.2
	Product Dimension without Stand (WxDxH) (inch)	21.25 x 12.67 x 2.92
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	203 x 203 x 145.4
	Stand Dimension (WxDxH) (inch)	7.99 x 7.99 x 5.72
Dimension & Weight	Inside Carton Dimensions (WxDxH) (mm)	600 x 140 x 400
	Inside Carton Dimensions (WxDxH) (inch)	23.62 x 5.51 x 15.75
	Weight (Net kg)	2.95
	Weight (Gross kg)	4.39
Weight	Weight Without Stand (kg)	2.57
Warranty	Warranty	36M
Model	Part No	9S6-3PB0CM-009
	Color	ID1/Black-Black