

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- PerfectEdge - el diseño de bisel ultrafino en los 4 lados permite a los usuarios sumergirse por completo en una configuración multimonitor
- Disfruta de entretenimiento de alta calidad con una tasa de refresco de 144 Hz más fluida.
- La pantalla con certificación TÜV garantiza la protección y la salud de la vista.
- La tecnología MSI EyesErgo con tecnología Anti-Flicker ayuda a prevenir la fatiga y el cansancio visual.
- MSI Eye-Q Check ayuda a realizar una autoevaluación de la vista y recuerda tomar descansos al usar el monitor durante largos periodos.
- El diseño compatible con montaje VESA proporciona una instalación ordenada, mejorando la comodidad y la organización del usuario.
- Mantén la versatilidad entre varios dispositivos utilizando múltiples fuentes de entrada, como puertos HDMI™ y D-Sub (VGA).
- Diseño estándar compatible con montaje VESA y ranura para accesorios.



1. 5-Way Navi-Key
2. DC-in
3. 1x HDMI™ 1.4b (FHD@144Hz)
4. 1x D-Sub (VGA)
5. Kensington-Lock

SPECIFICATION

Modelo	Part No	9S6-3PD2CM-049
	Color	ID1/Black-Black
Pantalla	Screen Size	24.5" (62.23cm)
	Active Display Area (mm)	543.744 (H) x 302.616 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.8~161.7 KHz(H) / 48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	85.7%/76.6%
	NTSC (CIE1931 area percentage/overlap)	71.6%/69%
	sRGB (CIE1976 area percentage/overlap)	99%/93%
	sRGB (CIE1931 area percentage/overlap)	103%/93%
	Adobe RGB (CIE1976 area percentage/overlap)	84.2%/80.5%
	Adobe RGB (CIE1931 area percentage/overlap)	75.2%/71.1%
	DCI-P3 (CIE1976 area percentage/overlap)	77.9%/77.9%
	DCI-P3 (CIE1931 area percentage/overlap)	75.2%/71.1%
	Rec.709 (CIE1976 area percentage/overlap)	99%/93%
	Rec.709 (CIE1931 area percentage/overlap)	103%/93%
	Rec.2020 (CIE1976 area percentage/overlap)	55.4%/55.4%
	Rec.2020 (CIE1931 area percentage/overlap)	52.2%/52.2%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Puertos E/S	D-Sub	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	2.3
Garantía	Warranty	36M
Alimentación	Power Type	External Adaptor 12V 2.5A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13 (Optional)



BUSINESS PRODUCTIVITY MONITOR

PRO MP251 E14L

PRO MP251 E14L

Accesorios	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	optional
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Diseño	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Tamaño y peso (producto)	Product Dimension with Stand (WxDxH) (mm)	557.2 x 419.3 x 182.4
	Product Dimension without Stand (WxDxH) (mm)	557.2 x 321.6 x 51.7
	Stand Dimension (WxDxH) (mm)	200.4 x 182.4 x 146.3
	Weight (Net kg)	2.89
	Weight Without Stand (kg)	2.58
Tamaño y peso (caja)	Inside Carton Dimension (WxDxH) (cm)	63 x 11.4 x 41.1
	Outer Carton Dimension (WxDxH) (cm)	64.8 x 13.2 x 44.3
	Weight (Gross kg)	4.89
Información sobre el código de barras	EAN	4711377409193