

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- PerfectEdge - el diseño de bisel delgado permite a los usuarios sumergirse completamente en una configuración de múltiples pantallas.
- Disfruta de entretenimiento de alta calidad con una frecuencia de actualización de 120Hz para una experiencia más fluida.
- Pantalla ampliada de 24,5 pulgadas - Disfruta del lienzo mejorado en un espacio limitado.
- El tamaño de pantalla ideal para la oficina y el escritorio se alinea con la zona de confort visual.
- Pantalla certificada por TÜV que garantiza la protección y salud de la vista.
- La tecnología MSI EyesErgo con tecnología Anti-Flicker ayuda a prevenir la fatiga y el cansancio ocular.
- MSI Eye-Q Check ayuda a realizar un autoexamen de la vista y recuerda tomar un descanso al usar el monitor durante mucho tiempo.
- Mantén la versatilidad entre diversos dispositivos utilizando múltiples fuentes de entrada, como puertos HDMI™, DisplayPort y D-Sub (VGA).
- Disfruta del entorno más limpio con un diseño de gestión de cables conveniente y desmontable.
- Diseño estándar montable en VESA y con ranura para accesorios.
- Dos altavoces integrados.



1. 1x DC-in
2. 1x DisplayPort 1.4a
3. 1x HDMI™ 2.0 (FHD@120Hz)
4. 1x D-Sub (VGA)
5. 1x Line-in
6. 1x Headphone-out
7. 1x Kensington Lock
8. 1x 5-way navigator



PRO MP251 E2

PRO MP251 E2

SPECIFICATION

Modelo	Part No	9S6-3PD2CM-009
	Color	ID1/Black-Black
Pantalla	Screen Size	24.5" (62.2cm)
	Active Display Area (mm)	543.744 x 302.616
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.704~132.12 KHz(H) / 48~120 Hz(V)
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	87%,79%
	NTSC (CIE1931 area percentage/overlap)	73%,71%
	sRGB (CIE1976 area percentage/overlap)	99%,95%
	sRGB (CIE1931 area percentage/overlap)	105%,96%
	Adobe RGB (CIE1976 area percentage/overlap)	85%,83%
	Adobe RGB (CIE1931 area percentage/overlap)	77%,74%
	DCI-P3 (CIE1976 area percentage/overlap)	79%,79%
	DCI-P3 (CIE1931 area percentage/overlap)	77%,74%
	Rec.709 (CIE1976 area percentage/overlap)	99%,95%
	Rec.709 (CIE1931 area percentage/overlap)	105%,96%
	Rec.2020 (CIE1976 area percentage/overlap)	57%/57%
	Rec.2020 (CIE1931 area percentage/overlap)	54%,54%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Puertos E/S	D-Sub	1
	Line-in	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	2x 2W
	HDMI	1
	HDMI version	2.0
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	1.3
Garantía	Warranty	36M
Alimentación	Power Type	External Adaptor 12V 2.5A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13



PRO MP251 E2

PRO MP251 E2

Accesorios	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Diseño	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Tamaño y peso (producto)	Product Dimension with Stand (WxDxH) (mm)	556.89 x 188.2 x 413.91
	Product Dimension without Stand (WxDxH) (mm)	556.89 x 42.94 x 321.49
	Stand Dimension (WxDxH) (mm)	218.84 x 188.2 x 146.22
	Weight (Net kg)	2.7
	Weight Without Stand (kg)	2.35
Tamaño y peso (caja)	Inside Carton Dimension (WxDxH) (cm)	63 x 14.2 x 41.1
	Outer Carton Dimension (WxDxH) (cm)	64.8 x 16 x 44.3
	Weight (Gross kg)	4.9
Información sobre el código de barras	EAN	4711377238502