

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- PerfectEdge - el diseño de bisel delgado en los cuatro lados permite a los usuarios sumergirse completamente en una configuración de múltiples pantallas.
- Disfruta de entretenimiento de alta calidad con una frecuencia de actualización de 120Hz más fluida.
- Pantalla Ampliada de 24.5 pulgadas - Disfruta del lienzo ampliado en espacios limitados.
- El mejor tamaño de pantalla para la oficina y el escritorio de trabajo, alineado con la zona de confort visual.
- Pantalla certificada por TÜV que garantiza la protección y salud de la vista.
- Tecnología MSI EyesErgo con tecnología Anti-Flicker que ayuda a prevenir la fatiga ocular y el cansancio.
- MSI Eye-Q Check ayuda a realizar un auto-chequeo de los ojos y recuerda tomar descansos durante el uso prolongado del monitor.
- Mantén la versatilidad entre diversos dispositivos utilizando múltiples fuentes de entrada, como puertos HDMI™ y D-Sub (VGA).
- Diseño estándar montable en VESA.



1. 5-way navigator
2. 1x DC Jack
3. 1x HDMI™ 1.4b (FHD@120Hz)
4. 1x D-Sub (VGA)
5. 1x Kensington Lock



SPECIFICATION

Modelo	Part No	9S6-3PD2CM-029
	Color	ID1/Black-Black
Pantalla	Screen Size	24.5" (62.23cm)
	Active Display Area (mm)	543.744 (H) x 302.616 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	250
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	TBD
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	TBD/TBD
	NTSC (CIE1931 area percentage/overlap)	TBD/TBD
	sRGB (CIE1976 area percentage/overlap)	TBD/TBD
	sRGB (CIE1931 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1976 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1931 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1976 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1931 area percentage/overlap)	TBD/TBD
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Puertos E/S	D-Sub	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
Garantía	Warranty	36M
Alimentación	Power Type	External Adaptor 12V 2.5A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	TBD
	Off-mode Power Consumption (W)	TBD
	Energy Efficiency Rating	TBD



BUSINESS PRODUCTIVITY MONITOR

PRO MP251L E2

PRO MP251L E2

Accesorios	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	0
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Diseño	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Tamaño y peso (producto)	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	TBD
	Weight Without Stand (kg)	TBD
Tamaño y peso (caja)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	TBD
Información sobre el código de barras	EAN	4711377286794