

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- PerfectEdge: el diseño de bisel delgado en los cuatro lados permite a los usuarios sumergirse por completo en una configuración de múltiples pantallas.
- Disfruta de entretenimiento de alta calidad con una tasa de refresco más fluida de 144 Hz y AMD FreeSync™.
- La pantalla con certificación TÜV garantiza la protección y la salud de la vista.
- La tecnología MSI EyesErgo con tecnología Anti-Flicker ayuda a prevenir la fatiga y el cansancio ocular.
- MSI Eye-Q Check ayuda a realizar autocomprobaciones oculares y recuerda que hay que descansar cuando se utiliza el monitor durante mucho tiempo.
- El diseño montable en VESA proporciona una configuración ordenada, lo que mejora la comodidad y la organización del usuario.
- MSI Power Link permite encender el ordenador de sobremesa MSI con solo pulsar el botón de encendido del monitor.
- Mantén la versatilidad en varios dispositivos utilizando múltiples fuentes de entrada, como puertos HDMI™, DisplayPort y D-Sub (VGA).
- Diseño estándar con montaje VESA y ranura para accesorios.
- Dos altavoces integrados.



1. 5-Way Navi Key
2. AC-in
3. DisplayPort 1.2a
4. 1x HDMI™ 2.0 (FHD@144Hz)
5. 1x D-Sub (VGA)
6. 1x Line-in
7. 1x Headphone-out



SPECIFICATION

Modelo	Part No	9S6-3PE9CM-001
	Color	ID1/Black-Black
Pantalla	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	TBD
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/78%
	NTSC (CIE1931 area percentage/overlap)	78%/70%
	sRGB (CIE1976 area percentage/overlap)	116%/93%
	sRGB (CIE1931 area percentage/overlap)	113%/94%
	Adobe RGB (CIE1976 area percentage/overlap)	98%/83%
	Adobe RGB (CIE1931 area percentage/overlap)	82%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	90%/87%
	DCI-P3 (CIE1931 area percentage/overlap)	82%/80%
	Rec.709 (CIE1976 area percentage/overlap)	116%/93%
	Rec.709 (CIE1931 area percentage/overlap)	113%/94%
	Rec.2020 (CIE1976 area percentage/overlap)	64%/64%
	Rec.2020 (CIE1931 area percentage/overlap)	57%/57%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Puertos E/S	D-Sub	1
	Line-in	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	1
	HDMI version	2.0
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Garantía	Warranty	24M
Alimentación	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13



PRO MP271 E14A

PRO MP271 E14A

Acesorios	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	0
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Diseño	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Tamaño y peso (producto)	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	TBD
	Weight Without Stand (kg)	TBD
Tamaño y peso (caja)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	TBD
Información sobre el código de barras	EAN	4711377381697