

PATH TO THE FUTURE

Introducing the MSI MAG 2244F esports gaming monitor. This cutting-edge monitor features a 24-inch FHD display with a lightning-fast 200Hz refresh rate and a rapid 0.5ms (GtG, Min.) MPRT response time. With the MAG 244F, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

SELLING POINTS

- Dalle Rapid IPS pour des couleurs et une luminosité optimales
- Taux de rafraîchissement de 200 Hz pour un affichage sans ralentissement
- Temps de réponse gris à gris 0,5 ms pour des images sans déchirures ni saccades
- Nouvelle technologie AI Vision cadencée par l'IA pour mieux discerner les détails dans les zones sombres
- Réduction de la lumière bleue pour une utilisation confortable



1. 5-way Joystick Navigator
2. AC-in
3. HDMI™ 2.0b (FHD@200Hz)
4. DisplayPort 1.2a (HBR2)
5. Headphone out
6. Kensington lock



SPECIFICATION

Modèle	SKU Number	9S6-3BC51T-001
	Entity MKT Name	MAG 242F
	Part No	9S6-3BC51T-001
	Color	ID1/Black-Black
Affichage	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04(H) x 296.46(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~230 KHz(H) / 48~200 Hz(V)
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/80%
	NTSC (CIE1931 area percentage/overlap)	79%/73%
	sRGB (CIE1976 area percentage/overlap)	115%/98%
	sRGB (CIE1931 area percentage/overlap)	112%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	99%/86%
	Adobe RGB (CIE1931 area percentage/overlap)	83%/77%
	DCI-P3 (CIE1976 area percentage/overlap)	92%/89%
	DCI-P3 (CIE1931 area percentage/overlap)	83%/82%
	Rec.709 (CIE1976 area percentage/overlap)	115%/98%
	Rec.709 (CIE1931 area percentage/overlap)	112%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	67%/67%
	Rec.2020 (CIE1931 area percentage/overlap)	59%/59%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Ports E/S	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18 (SDR) 30 (HDR)
	Annual Energy Consumption (KWh)	27
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) G (HDR)
	Power Cord Type	C13

Accessoires	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	540.2 x 220.1 x 396.8
	Product Dimension without Stand (WxDxH) (mm)	540.2 x 52.7 x 322
	Stand Dimension (WxDxH) (mm)	318 x 220.1 x 140
	Weight (Net kg)	3.
	Weight Without Stand (kg)	2.6
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	60 x 12.3 x 41
	Outer Carton Dimension (WxDxH) (cm)	61.5 x 13.8 x 43.3
	Weight (Gross kg)	4.8
Code-barre	EAN	4711377289795