

### PATH TO THE FUTURE

Découvrez l'écran gaming esport MSI MAG 272F ! Cet écran de 27" à dalle Rapid IPS et résolution Full HD offre un taux de rafraîchissement de 200 Hz et un temps de réponse de 0,5 ms (gris à gris, minimum) qui vous permettent de prendre l'avantage sur vos adversaires dans toutes vos parties !



Picture and logos

### SELLING POINTS

- Dalle Rapid IPS pour des couleurs et une luminosité optimales
- Taux de rafraîchissement de 200 Hz et temps de réponse de 0,5 ms
- Technologie AMD FreeSync pour des images fluides sans saccades ni déchirures
- Nouvelle technologie AI Vision cadencée par l'IA pour mieux discerner les détails dans les zones sombres
- Réduction de la lumière bleue grâce à une solution logicielle



1. 5-way Joystick Navigator
2. AC-in
3. 2x HDMI™ 2.0b (FHD@200Hz)
4. Display Port 1.2a (HBR2)
5. Headphone out
6. Kensington Lock

**SPECIFICATION**

Modèle	Part No	9S6-3CE51T-001
	Color	ID1/Black-Black
Affichage	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	TBD
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/86%
	NTSC (CIE1931 area percentage/overlap)	86%/80%
	sRGB (CIE1976 area percentage/overlap)	115%/98%
	sRGB (CIE1931 area percentage/overlap)	121%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	98%/90%
	Adobe RGB (CIE1931 area percentage/overlap)	90%/84%
	DCI-P3 (CIE1976 area percentage/overlap)	91%/91%
	DCI-P3 (CIE1931 area percentage/overlap)	89%/89%
	Rec.709 (CIE1976 area percentage/overlap)	115%/98%
	Rec.709 (CIE1931 area percentage/overlap)	121%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	66%/66%
	Rec.2020 (CIE1931 area percentage/overlap)	64%/64%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
Ports E/S	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21 (SDR) 30 (HDR)
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) G (HDR)
	Power Cord Type	C13

Accessoires	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	612.6 x 249.8 x 440
	Product Dimension without Stand (WxDxH) (mm)	612.6 x 54 x 364.8
	Stand Dimension (WxDxH) (mm)	339.8 x 249.8 x 140.2
	Weight (Net kg)	3.9
	Weight Without Stand (kg)	3.5
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	66.8 x 13.1 x 44.6
	Outer Carton Dimension (WxDxH) (cm)	68.3 x 14.6 x 46.9
	Weight (Gross kg)	6.2
Code-barre	EAN	4711377289542