

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- Rapid VA Panel – Provides 0.5ms (GtG, Min.) response time, optimizes screen colors and brightness.
- 180Hz Refresh Rate – Respond faster with smoother frames.
- 0.5ms (GtG, Min.) Response Time – Eliminate screen tearing and choppy frame rates.
- AI Vision – The new AI Vision technology can not only reveal details in dark areas but also enhance overall brightness and saturate colors.
- Less Blue Light – Use a software solution to reduce the light emission in the blue-violet region of the blue light spectrum.



1. 5-Way Joystick Navigator
2. AC-in
3. 2 x HDMI™ 2.0b(WQHD@144Hz)
4. DisplayPort 1.4
5. Earphone out
6. Kensington Lock

SPECIFICATION

Modèle	Part No	9S6-3CD04H-051
	Color	ID1/Black-Black
Affichage	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	5000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	30~200 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	N/A
	NTSC (CIE1931 area percentage/overlap)	N/A
	sRGB (CIE1976 area percentage/overlap)	N/A
	sRGB (CIE1931 area percentage/overlap)	N/A
	Adobe RGB (CIE1976 area percentage/overlap)	N/A
	Adobe RGB (CIE1931 area percentage/overlap)	N/A
	DCI-P3 (CIE1976 area percentage/overlap)	N/A
	DCI-P3 (CIE1931 area percentage/overlap)	N/A
	Rec.709 (CIE1976 area percentage/overlap)	N/A
	Rec.709 (CIE1931 area percentage/overlap)	N/A
	Rec.2020 (CIE1976 area percentage/overlap)	N/A
	Rec.2020 (CIE1931 area percentage/overlap)	N/A
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Ports E/S	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	External Adaptor 19V 2.58A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C13	

Accessoires	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-20° ~ 20°
	Adjustment (Height)	0 ~ 110 mm
	VESA Mounting	75x75mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	611.5 x 214.0 x 428.7
	Product Dimension without Stand (WxDxH) (mm)	611.5 x 99.7 x 364.1
	Stand Dimension (WxDxH) (mm)	508.1 x 214.0 x 394.4
	Weight (Net kg)	5.7
	Weight Without Stand (kg)	3.8
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	8.38
Code-barre	EAN	4711377212786