

### PATH TO THE FUTURE

Découvrez l'écran gaming esports MSI MAG 275CQRF QD E2 qui arbore une dalle WQHD de 27" avec taux de rafraîchissement ultrarapide de 180 Hz et temps de réponse de 0,5 ms (gris à gris, minimum). Avec le MAG 275CQRF QD E2, préparez-vous à prendre l'avantage sur vos concurrents pendant toutes vos batailles.



Picture and logos

### SELLING POINTS

- Dalle Rapid VA avec taux de rafraîchissement de 180 Hz et temps de réponse de 0,5 ms
- Pied de support ajustable pour une expérience ergonomique
- Certification VESA DisplayHDR 400 pour des couleurs d'un réalisme impressionnant
- Suite MSI Gaming Intelligence™ avec fonctionnalités gaming basées sur l'IA
- Mise à jour des firmwares par l'intermédiaire d'un port USB pour plus de simplicité
- AI Vision pour des détails plus précis dans les zones sombres



1. 5-Way Joystick Navigator
2. DC-in
3. Earphone out
4. DisplayPort 1.4a
5. 2 x HDMI™ 2.0b(WQHD@144Hz)
6. USB Type-C (PD 15W)
7. USB 2.0 Type-B
8. 2 x USB 2.0 Type-A
9. Kensington Lock

**SPECIFICATION**

Modèle	SKU Number	9S6-3CD04H-027
	Part No	9S6-3CD04H-027
	Color	ID1/Black-Black
Affichage	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	5000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	90~248 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	130%/93%
	NTSC (CIE1931 area percentage/overlap)	105%/94%
	sRGB (CIE1976 area percentage/overlap)	150%/99%
	sRGB (CIE1931 area percentage/overlap)	150%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	125%/97%
	Adobe RGB (CIE1931 area percentage/overlap)	110%/98%
	DCI-P3 (CIE1976 area percentage/overlap)	117%/97%
	DCI-P3 (CIE1931 area percentage/overlap)	110%/94%
	Rec.709 (CIE1976 area percentage/overlap)	150%/99%
	Rec.709 (CIE1931 area percentage/overlap)	150%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	86%/83%
	Rec.2020 (CIE1931 area percentage/overlap)	79%/79%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Ports E/S	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	USB 2.0 Type A	2
	USB 2.0 Type B	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
	Garantie	Warranty
Alimentation	Power Type	External Adaptor 19V 4.74A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C5	

Accessoires	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-20° ~ 20°
	Adjustment (Height)	0 ~ 110 mm
	VESA Mounting	75x75mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	611.5 x 236.7 x 428.7
	Product Dimension without Stand (WxDxH) (mm)	611.5 x 99.7 x 364.1
	Stand Dimension (WxDxH) (mm)	508.1 x 236.7 x 394.4
	Weight (Net kg)	5.7
	Weight Without Stand (kg)	3.8
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	82.1 x 14.7 x 46.1
	Outer Carton Dimension (WxDxH) (cm)	83.6 x 16.1 x 48.5
	Weight (Gross kg)	8.3
Code-barre	EAN	4711377191838