

## PATH TO THE FUTURE


Découvrez l'écran gaming esport MSI MAG 275F ! Cet écran de 27" à dalle Rapid IPS et résolution Full HD offre un taux de rafraîchissement de 180 Hz et un temps de réponse de 0.5 ms qui vous permettent de prendre l'avantage sur vos adversaires dans toutes vos parties !



Picture and logos

## SELLING POINTS

- Dalle Rapid IPS pour des couleurs et une luminosité optimales
- Taux de rafraîchissement de 180 Hz pour un affichage sans ralentissement
- Temps de réponse gris à gris de 0,5 ms pour des images sans déchirures ni saccades
- Technologie AMD FreeSync™ pour des images extrêmement fluides
- Nouvelle technologie AI Vision cadencée par l'IA pour mieux discerner les détails dans les zones sombres



1. 5-Way Joystick Navigator
2. 2 x HDMI™ (2.0)
3. DisplayPort (1.2a)
4. Earphone out
5. Kensington Lock
6. AC-in

**SPECIFICATION**

Modèle	Part No	9S6-3CE21M-031
	Color	ID1/Black-Black
Affichage	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	52.7~198 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	90%/75%
	NTSC (CIE1931 area percentage/overlap)	78%/72%
	sRGB (CIE1976 area percentage/overlap)	115%/95%
	sRGB (CIE1931 area percentage/overlap)	115%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	88%/75%
	Adobe RGB (CIE1931 area percentage/overlap)	82%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	85%/80%
	DCI-P3 (CIE1931 area percentage/overlap)	82%/80%
	Rec.709 (CIE1976 area percentage/overlap)	115%/95%
	Rec.709 (CIE1931 area percentage/overlap)	115%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	62%/62%
	Rec.2020 (CIE1931 area percentage/overlap)	56%/56%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
Ports E/S	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

Accessoires	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	611.3 x 220.1 x 454.3
	Product Dimension without Stand (WxDxH) (mm)	611.3 x 56.6 x 362.6
	Stand Dimension (WxDxH) (mm)	318 x 220.1 x 138.3
	Weight (Net kg)	4.
	Weight Without Stand (kg)	3.6
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	68.4 x 12.9 x 46.3
	Outer Carton Dimension (WxDxH) (cm)	70.4 x 14.9 x 49.8
	Weight (Gross kg)	6.2
Code-barre	EAN	4711377331494