

## PATH TO THE FUTURE

Vivez intensément votre victoire avec l'écran gaming MAG 27C6F ! Avec une résolution de 1920 x 1080, un taux de rafraîchissement de 180 Hz et un temps de réponse gris à gris minimum de 0,5 ms, l'écran MAG 27C6F sera votre meilleur allié pour prendre l'avantage sur vos adversaires.



Picture and logos

## SELLING POINTS

- Dalle Rapid VA avec temps de réponse gris à gris minimum de 0,5 ms pour des couleurs et une luminosité optimales
- Taux de rafraîchissement de 180 Hz pour un affichage sans ralentissement
- Temps de réponse gris à gris minimum de 0,5 ms pour des images sans déchirures ni saccades
- AI Vision pour mieux discerner les détails dans les zones sombres mais également améliorer la luminosité et la saturation des couleurs
- Adaptive-Sync pour des images extrêmement fluides
- Technologie HDR qui améliore les contrastes et les ombres pour des images plus détaillées
- Réduction de la lumière bleue pour une utilisation confortable



1. Bouton de navigation à 5 direction
2. Entrée alimentation
3. 2 x HDMI™ (2.0b)
4. DisplayPort (1.4)
5. Sortie audio
6. Encoche Kensington

**SPECIFICATION**

Modèle	Part No	9S6-3CE11M-038
	Color	ID1/Black-Black
Affichage	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	53.04~199.08 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	80%/74%
	NTSC (CIE1931 area percentage/overlap)	70%/68%
	sRGB (CIE1976 area percentage/overlap)	93%/90%
	sRGB (CIE1931 area percentage/overlap)	99%/90%
	Adobe RGB (CIE1976 area percentage/overlap)	78%/78%
	Adobe RGB (CIE1931 area percentage/overlap)	72%/70%
	DCI-P3 (CIE1976 area percentage/overlap)	73%/73%
	DCI-P3 (CIE1931 area percentage/overlap)	72%/72%
	Rec.709 (CIE1976 area percentage/overlap)	93%/90%
	Rec.709 (CIE1931 area percentage/overlap)	99%/90%
	Rec.2020 (CIE1976 area percentage/overlap)	52%/52%
	Rec.2020 (CIE1931 area percentage/overlap)	50%/50%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	8 bits
Ports E/S	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

Accessoires	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	610.5 x 249.8 x 451.6
	Product Dimension without Stand (WxDxH) (mm)	610.5 x 90.4 x 362.5
	Stand Dimension (WxDxH) (mm)	339.8 x 249.7 x 142.7
	Weight (Net kg)	3.95
	Weight Without Stand (kg)	3.56
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	68.4 x 15.8 x 47.5
	Outer Carton Dimension (WxDxH) (cm)	70.4 x 17.8 x 50.8
	Weight (Gross kg)	6.51
Code-barre	EAN	4711377331425