

## PATH TO THE FUTURE



Picture and logos

## SELLING POINTS

- Dalle QD-OLED nouvelle génération pour des images d'une qualité incroyable
- Temps de réponse gris à gris ultrarapide de seulement 0,03 ms et taux de rafraîchissement de 165 Hz
- QD Premium Color pour assurer des couleurs qui répondent aux normes du marché, avec valeur Delta E ≤ 2
- Norme VESA DisplayHDR True Black 400 pour des visuels HDR à couper le souffle
- MSI OLED Care 2.0 pour réduire les risques de brûlures de la dalle OLED
- Mode Console avec port HDMI™ 2.1 (4K @ 165 Hz) avec bande passante totale de 48 Gb/s
- Pied de support réglable pour trouver la position la plus confortable pour jouer
- Garantie OLED 3 ans contre les brûlures



1. AC-in
2. 5-way Joystick Navigator
3. 2 x HDMI™ 2.1(UHD@165Hz)
4. Display Port 1.4a
5. USB Type-C (PD 15W)
6. Earphone out
7. Kensington lock

## SPECIFICATION

|              |                                             |                              |
|--------------|---------------------------------------------|------------------------------|
| Modèle       | Part No                                     | 9S6-3DD39T-027               |
|              | Color                                       | ID1/Black-Black              |
| Affichage    | Screen Size                                 | 31.5" (80 cm)                |
|              | Active Display Area (mm)                    | 699.48(H) x 394.73(V)        |
|              | Curvature                                   | Flat                         |
|              | Panel Type                                  | QD-OLED                      |
|              | Resolution                                  | 3840x2160 (UHD)              |
|              | Pixel pitch (mm)                            | 0.1814(H)x0.1814(V)          |
|              | Aspect Ratio                                | 16:9                         |
|              | Dynamic Refresh Rate technology             | Adaptive-Sync                |
|              | Dynamic Refresh Rate Activated Range        | 48~165Hz                     |
|              | HDR (High dynamic range)                    | True Black 400               |
|              | SDR Brightness (nits)                       | 250                          |
|              | HDR Brightness (Peak nits)                  | 1000                         |
|              | Contrast Ratio                              | 1500000:1                    |
|              | Signal Frequency                            | 30~390 KHz(H) / 48~165 Hz(V) |
|              | Refresh Rate                                | 165HZ                        |
|              | Response Time (GTG)                         | 0.03ms                       |
|              | View Angles                                 | 178°(H)/178°(V)              |
|              | NTSC (CIE1976 area percentage/overlap)      | 120.5%/93.8%                 |
|              | NTSC (CIE1931 area percentage/overlap)      | 103.6%/91.5%                 |
|              | sRGB (CIE1976 area percentage/overlap)      | 138.2%/100%                  |
|              | sRGB (CIE1931 area percentage/overlap)      | 146.2%/100%                  |
|              | Adobe RGB (CIE1976 area percentage/overlap) | 118.4%/97.5%                 |
|              | Adobe RGB (CIE1931 area percentage/overlap) | 108.4%/94%                   |
|              | DCI-P3 (CIE1976 area percentage/overlap)    | 110.1%/99%                   |
|              | DCI-P3 (CIE1931 area percentage/overlap)    | 107.8%/98.4%                 |
|              | Rec.709 (CIE1976 area percentage/overlap)   | 138.2%/100%                  |
|              | Rec.709 (CIE1931 area percentage/overlap)   | 146.2%/100%                  |
|              | Rec.2020 (CIE1976 area percentage/overlap)  | 80.2%/80.2%                  |
|              | Rec.2020 (CIE1931 area percentage/overlap)  | 77.3%/77.3%                  |
|              | Surface Treatment                           | Anti-Reflection              |
|              | Display Colors                              | 1.07B                        |
|              | Color bit                                   | 10 bits                      |
| Ports E/S    | USB Type C (DisplayPort Alternate)          | 1                            |
|              | Headphone-out                               | 1                            |
|              | Lock type                                   | Kensington Lock              |
|              | HDMI                                        | 2                            |
|              | HDMI version                                | 2.1                          |
|              | HDMI HDCP version                           | 2.3                          |
|              | DisplayPort                                 | 1                            |
|              | DisplayPort version                         | 1.4a                         |
|              | DisplayPort HDCP version                    | 2.3                          |
| Garantie     | Warranty                                    | 36M                          |
| Alimentation | Power Type                                  | Power Cable                  |
|              | Power Input                                 | 100~240V, 50/60Hz            |
|              | On-mode Power Consumption (KWh/1000h)       | 50                           |
|              | Standby-mode Power Consumption (W)          | 0.5                          |
|              | Off-mode Power Consumption (W)              | 0.3                          |
|              | Energy Efficiency Rating                    | G                            |
|              | Power Cord Type                             | C13                          |



É C R A N S   G A M I N G

MAG 321UP QD-OLED

M A G   3 2 1 U P   Q D - O L E D

|                              |                                              |                    |
|------------------------------|----------------------------------------------|--------------------|
| Accessoires                  | DisplayPort Cable                            | 1                  |
|                              | HDMI Cable                                   | 1                  |
|                              | DVI Cable                                    | 0                  |
|                              | USB Type A to Type B Cable                   | 0                  |
|                              | USB Type C to Type A Cable                   | 0                  |
|                              | USB Type C to Type C Cable                   | 0                  |
|                              | Thunderbolt Cable                            | 0                  |
|                              | VGA Cable                                    | 0                  |
|                              | 3.5mm audio Cable                            | 0                  |
|                              | 3.5mm combo audio Cable                      | 0                  |
|                              | 3.5mm Mic Cable                              | 0                  |
|                              | Power Cord                                   | 1                  |
|                              | AC Adaptor                                   | 0                  |
|                              | Quick Guide                                  | 1                  |
|                              | Warranty Card                                | 0                  |
|                              | Mouse Bungee Unit                            | 0                  |
| Design                       | Adjustment (Tilt)                            | -5° ~ 15°          |
|                              | Adjustment (Swivel)                          | -30° ~ 30°         |
|                              | Adjustment (Height)                          | 0 ~ 110 mm         |
|                              | Adjustment (Pivot)                           | -10° ~ 10°         |
|                              | VESA Mounting                                | 100x100mm          |
| Dimension & Weight (product) | Product Dimension with Stand (WxDxH) (mm)    | 717 x 242 x 457    |
|                              | Product Dimension without Stand (WxDxH) (mm) | 717 x 72 x 419     |
|                              | Stand Dimension (WxDxH) (mm)                 | 309 x 242 x 391    |
|                              | Weight (Net kg)                              | 9.1                |
|                              | Weight Without Stand (kg)                    | 6.3                |
| Dimensions et poids (carton) | Inside Carton Dimension (WxDxH) (cm)         | 97.2 x 18.5 x 51.3 |
|                              | Outer Carton Dimension (WxDxH) (cm)          | 99 x 20 x 53.8     |
|                              | Weight (Gross kg)                            | 11.8               |
| Code-barre                   | EAN                                          | 4711377332552      |