

PATH TO THE FUTURE

Découvrez l'écran gaming esports MSI MPG 275CQRXF qui arbore une dalle WQHD de 27" avec taux de rafraîchissement ultrarapide de 240 Hz et temps de réponse de 0,5 ms (gris à gris, minimum). Avec le MPG 275CQRXF, préparez-vous à prendre l'avantage sur vos concurrents pendant toutes vos batailles.



Picture and logos

SELLING POINTS

- Dalle Rapid VA avec taux de rafraîchissement de 240 Hz et temps de réponse de 0,5 ms
- Pied de support ajustable pour une expérience ergonomique
- Certification VESA DisplayHDR 400 pour des couleurs d'un réalisme impressionnant
- Suite MSI Gaming Intelligence™ avec fonctionnalités gaming basées sur l'IA
- Mise à jour des firmwares par l'intermédiaire d'un port USB pour plus de simplicité
- AI Vision pour des détails plus précis dans les zones sombres



1. 5-way Joystick Navigator
2. DC-in
3. Earphone out
4. Display Port 1.4a
5. 2x HDMI™ 2.0b (WQHD@144Hz)
6. USB 2.0 Type-C (DP alt.) w/ 98W PD
7. USB 2.0 Type-B
8. 2 x USB 2.0 Type-A
9. Kensington Lock

SPECIFICATION

Modèle	Part No	9S6-3CD04H-072
	Color	ID1/Black-Black
Affichage	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.74(H) x 335.66(V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	DisplayHDR 400
	SDR Brightness (nits)	350
	HDR Brightness (Peak nits)	400
	Contrast Ratio	4000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	70.55~352.49 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	104%/87%
	NTSC (CIE1931 area percentage/overlap)	89%/83%
	sRGB (CIE1976 area percentage/overlap)	120%/99%
	sRGB (CIE1931 area percentage/overlap)	125%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	103%/91%
	Adobe RGB (CIE1931 area percentage/overlap)	93%/87%
	DCI-P3 (CIE1976 area percentage/overlap)	95%/94%
	DCI-P3 (CIE1931 area percentage/overlap)	93%/92%
	Rec.709 (CIE1976 area percentage/overlap)	120%/99%
	Rec.709 (CIE1931 area percentage/overlap)	125%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	69%/69%
	Rec.2020 (CIE1931 area percentage/overlap)	67%/67%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
Ports E/S	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	USB 2.0 Type A	2
	USB 2.0 Type B	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
	Garantie	Warranty
Alimentation	Power Type	External Adaptor 19V 7.89A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C5	

Accessoires	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-20° ~ 20°
	Adjustment (Height)	0 ~ 110 mm
	VESA Mounting	75x75mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	611.5 x 236.7 x 428.7
	Product Dimension without Stand (WxDxH) (mm)	611.5 x 99.7 x 364.1
	Stand Dimension (WxDxH) (mm)	508.1 x 236.7 x 394.4
	Weight (Net kg)	5.8
	Weight Without Stand (kg)	3.95
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	82.1 x 14.7 x 46.1
	Outer Carton Dimension (WxDxH) (cm)	83.6 x 16.1 x 48.5
	Weight (Gross kg)	8.3
Code-barre	EAN	4711377330978