

PATH TO THE FUTURE

L'écran gaming MSI MPG 322URX QD-OLED arbore une dalle QD-OLED 32" à résolution 3840 x 2160 (4K UHD) et taux de rafraîchissement de 240 Hz pour des images ultrafluides. Il est parfait pour les gamers compétitifs à la recherche d'immersion.



Picture and logos

SELLING POINTS

- Dalle QD-OLED de 3^e génération pour une qualité d'image impressionnante et un temps de réponse rapide
- DisplayPort 2.1a (UHBR20) pour une bande passante allant jusqu'à 80 Gb/s permettant aux gamers de profiter d'une expérience 4K en 240 Hz en natif et sans pertes
- Temps de réponse ultrarapide de 0,03 ms et taux de rafraîchissement de 240 Hz
- QD Premium Color qui assure des couleurs fidèles et Delta E ≤ 2
- Certification VESA DisplayHDR True Black 400
- MSI OLED Care 2.0 qui réduit les risques de brûlures sur la dalle OLED
- Mode Console avec port HDMI™ 2.1 (UHD@240Hz) et bande passante totale de 48 Gb/s
- Garantie 3 ans incluant la protection contre la brûlure de la dalle



1. Earphone out
2. 2 x HDMI™ 2.1 (UHD@240Hz)
3. Display Port 2.1
4. USB Type-C (PD 98W)
5. USB Type-B
6. 2 x USB Type-A
7. 5-way Joystick Navigator
8. AC-in
9. Kensington lock



SPECIFICATION

Modèle	Part No	9S6-3DD29A-016
	Color	ID1/Black-Black
Affichage	Screen Size	31.5" (80 cm)
	Active Display Area (mm)	699.48(H) x 394.73(V)
	Curvature	Flat
	Panel Type	QD-OLED
	Resolution	3840x2160 (UHD)
	Pixel pitch (mm)	0.1814(H)x0.1814(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	True Black 400
	SDR Brightness (nits)	250
	HDR Brightness (Peak nits)	1000
	Contrast Ratio	1500000:1
	Signal Frequency	TBD
	Refresh Rate	240HZ
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	120.5%/93.8%
	NTSC (CIE1931 area percentage/overlap)	103.6%/91.5%
	sRGB (CIE1976 area percentage/overlap)	138.2%/100%
	sRGB (CIE1931 area percentage/overlap)	146.2%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	118.4%/97.5%
	Adobe RGB (CIE1931 area percentage/overlap)	108.4%/94%
	DCI-P3 (CIE1976 area percentage/overlap)	110.1%/99%
	DCI-P3 (CIE1931 area percentage/overlap)	107.8%/98.4%
	Rec.709 (CIE1976 area percentage/overlap)	138.2%/100%
	Rec.709 (CIE1931 area percentage/overlap)	146.2%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80.2%/80.2%
	Rec.2020 (CIE1931 area percentage/overlap)	77.3%/77.3%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits
Ports E/S	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	USB 3.2 Gen 1 Type A	2
	USB 3.2 Gen 1 Type B	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.1
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	2.1
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	N/A
	Annual Energy Consumption (KWh)	N/A
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
	Power Cord Type	C13



É C R A N S G A M I N G

MPG 322URX QD-OLED

MPG 322URX QD-OLED

Accessoires	DisplayPort Cable	1
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 15°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 110 mm
	Adjustment (Pivot)	-10° ~ 10°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	N/A
Code-barre	EAN	4711377261197