

Finesse, élégance et fluidité



Picture and logos

SELLING POINTS

- Design PerfectEdge avec quatre bords d'écran ultrafins pour une meilleure immersion
- Taux de rafraîchissement de 144 Hz et technologie Adaptive Sync pour une meilleure expérience visuelle
- Certification TÜV qui assure une bonne protection des yeux
- Technologie MSI EyesErgo avec technologie antiscintillement pour réduire la fatigue oculaire
- Fonction MSI Eye-Q Check pour prendre soin de vos yeux et vous rappeler de faire une pause
- MSI Power Link pour allumer votre PC et votre écran en même temps
- Connectique polyvalente avec ports HDMI™ et Type-C
- Support de la norme de fixation VESA et fente pour accessoires
- Deux haut-parleurs intégrés



1. Bouton de navigation à 5 directions
2. Entrée alimentation
3. 1 x HDMI™ 2.0 (FHD @ 144 Hz)
4. 1 x Type-C (DP alt.) avec fonction Power Delivery 15 W
5. 1 x sortie audio
6. 1 x encoche Kensington

SPECIFICATION

Modèle	Part No	9S6-3PE8CM-001
	Color	ID1/Black-Black
Affichage	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	TBD
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100%/78%
	NTSC (CIE1931 area percentage/overlap)	78%/70%
	sRGB (CIE1976 area percentage/overlap)	116%/93%
	sRGB (CIE1931 area percentage/overlap)	113%/94%
	Adobe RGB (CIE1976 area percentage/overlap)	98%/83%
	Adobe RGB (CIE1931 area percentage/overlap)	82%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	90%/87%
	DCI-P3 (CIE1931 area percentage/overlap)	82%/80%
	Rec.709 (CIE1976 area percentage/overlap)	116%/93%
	Rec.709 (CIE1931 area percentage/overlap)	113%/94%
	Rec.2020 (CIE1976 area percentage/overlap)	64%/64%
	Rec.2020 (CIE1931 area percentage/overlap)	57%/57%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Ports E/S	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	1
	HDMI version	2.0
	HDMI HDCP version	2.3
Garantie	Warranty	36M
Alimentation	Power Type	TBD
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Annual Energy Consumption (KWh)	31
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
	Power Cord Type	C13

Accessoires	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Dimensions et poids (carton)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	N/A
Code-barre	EAN	4711377376792