

MAG 272QPW QD-OLED X28

MAG 272QPW QD-OLED X28

PATH TO THE FUTURE


The MAG 272QPW QD-OLED X28 gaming monitor with 27 inch of QD-OLED, 2K WQHD display, a lightning-fast 280Hz refresh rate, and a rapid 0.03ms response time. With the MAG 272QPW QD-OLED X28, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

SELLING POINTS

- 3rd Panel QD-OLED Gen Dengan kualitas gambar yang menakjubkan dan waktu respons yang cepat.
- Waktu respons GtG 0,03 ms tercepat dan kecepatan penyegaran 280 Hz.
- QD Premium Color Memastikan warna memenuhi standar pasar Delta E≤2.
- Visual HDR yang luar biasa VESA DisplayHDR True Black 400.
- Gerakan Sebening Kristal Bersertifikasi VESA ClearMR 15000.
- MSI OLED Care 2.0 Mengurangi risiko gambar OLED lengket / terbakar.
- Mode Konsol Dioptimalkan untuk kompatibilitas yang mulus dengan konsol game seperti PS5 dan Xbox Series X|S
- Garansi Burn-In 3 Tahun Termasuk perlindungan untuk burn-in OLED.



- 1. Headphone-out
- 2. 2x HDMI™ 2.1 (WQHD@280Hz)
- 3. DisplayPort 1.4a (HBR3)
- **4.** USB Type-C (15W PD)
- 5. 5-Way Navigator
- 6. AC-in
- 7. Kensington Lock





MAG 272QPW QD-OLED X28

MAG 272QPW QD-OLED X28

SPECIFICATION

Model	SKU Number	9S6-3CD79A-040
	Entity MKT Name	MAG 272QPW QD-OLED X28
	Part No	9S6-3CD79A-040
	Color	ID1/White-White
	Screen Size	26.5" (67.31 cm)
	Active Display Area (mm)	590.42(H) x 333.72(V)
	Curvature	Flat
		QD-OLED
	Panel Type	
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2292(H)x0.2292(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	NVIDIA G-SYNC Compatible / AMD FreeSync™ Premium Pro
Display	Dynamic Refresh Rate Activated Range	48~280Hz
	HDR (High dynamic range)	VESA DisplayHDR True Black 400
	SDR Brightness (nits)	250
	HDR Brightness (Peak nits)	1000
	Contrast Ratio	1500000:1
	Signal Frequency	30~450.8 KHz(H) / 48~280 Hz(V)
	Refresh Rate	280Hz
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	121%/95%
	NTSC (CIE1931 area percentage/overlap)	105%/92%
	sRGB (CIE1976 area percentage/overlap)	138%/100%
	sRGB (CIE1970 area percentage/overlap)	
		148%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	119%/98%
	Adobe RGB (CIE1931 area percentage/overlap)	109%/95%
	DCI-P3 (CIE1976 area percentage/overlap)	110%/99%
	DCI-P3 (CIE1931 area percentage/overlap)	109%/99%
	Rec.709 (CIE1976 area percentage/overlap)	138%/100%
	Rec.709 (CIE1931 area percentage/overlap)	148%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80%/80%
	Rec.2020 (CIE1931 area percentage/overlap)	78%/78%
	Surface Treatment	Anti-Reflection
I/O Ports	Display Colors	1.07B
	Color bit	10 bits
	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.1
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
vvarratity	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	•	
Power	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C13





MAG 272QPW QD-OLED X28

MAG 272QPW QD-OLED X28

D: 1 D 1 C 11	1
• •	1
112.11.20.012	0
	0
	0
USB Type C to Type A Cable	0
USB Type C to Type C Cable	0
Thunderbolt Cable	0
VGA Cable	0
3.5mm audio Cable	0
3.5mm combo audio Cable	0
3.5mm Mic Cable	0
Power Cord	1
AC Adaptor	0
Quick Guide	1
Warranty Card	0
Mouse Bungee Unit	0
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Height)	0 ~ 110 mm
Adjustment (Pivot)	-90° ~ 90°
VESA Mounting	100x100mm
Product Dimension with Stand (WxDxH) (mm)	611.1 x 241.9 x 532.84
Product Dimension without Stand (WxDxH) (mm)	611.1 x 69.3 x 357.2
Stand Dimension (WxDxH) (mm)	308.67 x 241.9 x 432.1
Weight (Net kg)	6.8
Weight Without Stand (kg)	4.1
Inside Carton Dimension (WxDxH) (cm)	82 x 16.9 x 51.3
Outer Carton Dimension (WxDxH) (cm)	83.3 x 18.2 x 53.5
	10.49
EAN	4711377319751
	Thunderbolt Cable VGA Cable 3.5mm audio Cable 3.5mm combo audio Cable 3.5mm Mic Cable Power Cord AC Adaptor Quick Guide Warranty Card Mouse Bungee Unit Adjustment (Tilt) Adjustment (Swivel) Adjustment (Height) Adjustment (Pivot) VESA Mounting Product Dimension with Stand (WxDxH) (mm) Product Dimension without Stand (WxDxH) (mm) Stand Dimension (WxDxH) (mm) Weight (Net kg) Unside Carton Dimension (WxDxH) (cm) Outer Carton Dimension (WxDxH) (cm) Weight (Gross kg)