

Be Your Window To The World



Picture and logos

SELLING POINTS

- 21:9 Kurvatur 1500R menghadirkan pengalaman menonton yang imersif dan nyaman dengan mengurangi distorsi serta mencakup bidang pandang yang lebih luas.
- Siap untuk bermain game ringan dengan refresh rate tinggi 120Hz & dukungan Adaptive-Sync.
- Koneksi USB Type-C bawaan dengan fungsi pengisian daya 98W memungkinkan Anda menghubungkan dan mengisi daya perangkat dengan mudah.
- Mode PIP/PBP memberikan efisiensi lebih baik bagi para kreator saat dibutuhkan.
- Layar bersertifikasi TÜV memastikan perlindungan dan kesehatan mata pengguna.
- Teknologi MSI EyeSight dengan Anti-Flicker membantu mencegah ketegangan dan kelelahan mata.
- MSI Eye-Q Check membantu pengguna melakukan pemeriksaan mandiri pada mata & mengingatkan untuk beristirahat saat menggunakan monitor dalam waktu lama.
- Stand monitor ini dirancang dengan fitur ergonomis, termasuk penyesuaian kemiringan, putaran, dan ketinggian.
- Pertahankan fleksibilitas penggunaan di berbagai perangkat dengan memanfaatkan beberapa sumber input, seperti port Type-C, HDMI™, dan DP.
- Nikmati lingkungan yang lebih rapi berkat desain manajemen kabel yang praktis dan dapat dilepas.
- Dilengkapi dengan dua speaker bawaan.



1. 1x DC Jack
2. 1x Headphone-out
3. 2x HDMI 2.0b
4. 1x DisplayPort 1.4a
5. 1x Type-C (DP Alt.) w/ 98W PD
6. 1x USB 5Gbps Type-B
7. 2x USB 5Gbps Type-A
8. 1x Kensington Lock
9. OSD Button

SPECIFICATION

| | | |
|-----------------|---|-----------------------------------|
| Model | Part No | 9S6-3PC59H-006 |
| | Color | ID1/Black-Black |
| Display | Screen Size | 34" (86.36 cm) |
| | Active Display Area (mm) | 797.22(H) x 333.72(V) |
| | Curvature | Curve 1500R |
| | Panel Type | VA |
| | Resolution | 3440x1440 (UWQHD) |
| | Pixel pitch (mm) | 0.23175(H)x0.23175(V) |
| | Aspect Ratio | 21:9 |
| | Dynamic Refresh Rate technology | Adaptive-Sync |
| | Dynamic Refresh Rate Activated Range | 48~120Hz |
| | HDR (High dynamic range) | HDR Ready |
| | SDR Brightness (nits) | 300 |
| | Contrast Ratio | 3500:1 |
| | DCR (Dynamic Contrast Ratio) | 100000000:1 |
| | Signal Frequency | 70.73~178.8 KHz(H) / 48~120 Hz(V) |
| | Refresh Rate | 120Hz |
| | Response Time (MPRT) | 1ms(MPRT) |
| | Response Time (GTG) | 4ms |
| | View Angles | 178°(H)/178°(V) |
| | NTSC (CIE1976 area percentage/overlap) | 104%/85% |
| | NTSC (CIE1931 area percentage/overlap) | 87%/80% |
| | sRGB (CIE1976 area percentage/overlap) | 119%/99% |
| | sRGB (CIE1931 area percentage/overlap) | 122%/99% |
| | Adobe RGB (CIE1976 area percentage/overlap) | 102%/92% |
| | Adobe RGB (CIE1931 area percentage/overlap) | 91%/85% |
| | DCI-P3 (CIE1976 area percentage/overlap) | 95%/95% |
| | DCI-P3 (CIE1931 area percentage/overlap) | 90%/90% |
| | Rec.709 (CIE1976 area percentage/overlap) | 119%/99% |
| | Rec.709 (CIE1931 area percentage/overlap) | 122%/99% |
| | Rec.2020 (CIE1976 area percentage/overlap) | 69%/69% |
| | Rec.2020 (CIE1931 area percentage/overlap) | 65%/65% |
| | Surface Treatment | Anti-glare |
| | Display Colors | 1.07B |
| | Color bit | 10 bits (8 bits + FRC) |
| I/O Ports | USB Type C (DisplayPort Alternate) | 1 |
| | Headphone-out | 1 |
| | USB 3.2 Gen 1 Type A | 2 |
| | USB 3.2 Gen 1 Type B | 1 |
| | Card reader | N/A |
| | Lock type | Kensington Lock |
| | Speaker | 2 |
| | HDMI | 2 |
| | HDMI version | 2.0b |
| | HDMI HDCP version | 2.3 |
| | DisplayPort | 1 |
| | DisplayPort version | 1.4a |
| | DisplayPort HDCP version | 2.3 |
| | Warranty | Warranty |
| Power | Power Type | External Adaptor 19V 9.5A |
| | Power Input | 100~240V, 50/60Hz |
| | On-mode Power Consumption (KWh/1000h) | 31 |
| | Annual Energy Consumption (KWh) | 31 |
| | Standby-mode Power Consumption (W) | 0.5 |
| | Off-mode Power Consumption (W) | 0.3 |
| | Energy Efficiency Rating | F |
| Power Cord Type | C5 | |

| | | |
|------------------------------|--|-----------------------|
| In The Box | DisplayPort Cable | 1 |
| | HDMI Cable | 0 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 1 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | 3.5mm Mic Cable | 0 |
| | Power Cord | 1 |
| | AC Adaptor | 1 |
| | Quick Guide | 1 |
| | Warranty Card | 0 |
| Mouse Bungee Unit | 0 | |
| Design | Adjustment (Tilt) | -5° ~ 20° |
| | Adjustment (Swivel) | -30° ~ 30° |
| | Adjustment (Height) | 0 ~ 110 mm |
| | Adjustment (Pivot) | -5° ~ 5° |
| | VESA Mounting | 75x75mm |
| Dimension & Weight (product) | Product Dimension with Stand (WxDxH) (mm) | 808.6 x 250.6 x 424.1 |
| | Product Dimension without Stand (WxDxH) (mm) | 808 x 125.3 x 362.4 |
| | Stand Dimension (WxDxH) (mm) | 335.9 x 250.6 x 423.2 |
| | Weight (Net kg) | 8.05 |
| | Weight Without Stand (kg) | 5.45 |
| Dimension & Weight (box) | Inside Carton Dimension (WxDxH) (cm) | 94.5 x 24.5 x 51 |
| | Outer Carton Dimension (WxDxH) (cm) | 96 x 25.8 x 53.4 |
| | Weight (Gross kg) | 11.9 |
| Barcode Info | EAN | 4711377151887 |