BUSINESS PRODUCTIVITY MONITOR

PRO MP225 E12L

PRO MP225 E12L

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- Enjoy the high-quality entertainment with a smoother 120Hz high refresh rate.
- TÜV certified display ensures the protection and health of eyesight.
- MSI EyesErgo technology with Anti-Flicker technology helps prevent eye strain and fatigue.
- MSI Eye-Q Check helps have self-check eyes & reminds to take a rest while using the monitor for a long time.
- VESA Mountable design provides a tidy setup, enhancing user comfort and organization.
- Maintain versatility across various devices by utilizing multiple input sources, such as HDMI™ and D-Sub(VGA) ports.
- Standard VESA mountable & Accessory Slot design.



1. 5-Way Navi Key
2. AC-in
3. 1x HDMI™ 1.4b (FHD@120Hz)
4. 1xD-Sub (VGA)
5. Kensington Lock

"2026-11-20 Changes to the product specifications and errors excepted. The product presentation may differ from the product. Microsoft, Windows, the Windows logo, and DirectX are trademarks or registered trademarks of Microsoft Corporation in the United States and / or other countries. Intel, the Intel logo, Intel Inside, the Intel Inside logo, Intel Core and Core Inside are trademarks of Intel Corporation in the US and other countries. Other trademarks and trade names refer to the respective owners or their products."

BUSINESS PRODUCTIVITY MONITOR

PRO MP225 E12L

PRO MP225 E12L

SPECIFICATION

Model	Part No	9S6-3PE0CM-060
	Color	ID1/Black-Black
Display	Screen Size	21.45" (54.48 cm)
	Active Display Area (mm)	476.064(H)x 267.786(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.24795(H)x0.24795(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~120Hz
	SDR Brightness (nits)	300
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	54.2~121.5 KHz(H) / 48~120 Hz(V)
	Refresh Rate	120Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	14ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	103%/90%
	NTSC (CIE1931 area percentage/overlap)	89%/84%
	sRGB (CIE1976 area percentage/overlap)	119%/98%
	sRGB (CIE1931 area percentage/overlap)	126%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	102%/93%
	Adobe RGB (CIE1931 area percentage/overlap)	93%/87%
	DCI-P3 (CIE1976 area percentage/overlap)	94%/93%
	DCI-P3 (CIE1931 area percentage/overlap)	93%/92%
	Rec.709 (CIE1976 area percentage/overlap)	119%/98%
	Rec.709 (CIE1931 area percentage/overlap)	126%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	69%/69%
	Rec.2020 (CIE1931 area percentage/overlap)	66%/66%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	D-Sub	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	110~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	15
	Annual Energy Consumption (KWh)	22
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13

"2026-11-20 Changes to the product specifications and errors excepted. The product presentation may differ from the product. Microsoft, Windows, the Windows logo, and DirectX are trademarks or registered trademarks of Microsoft Corporation in the United States and / or other countries. Intel, the Intel logo, Intel Inside, the Intel Inside logo, Intel Core and Core Inside are trademarks of Intel Corporation in the US and other countries. Other trademarks and trade names refer to the respective owners or their products."

PRO MP225 E12L

PRO MP225 E12L

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	489.4 x 182.36 x 384.77
	Product Dimension without Stand (WxDxH) (mm)	489.4 x 53.05 x 291.51
	Stand Dimension (WxDxH) (mm)	200.43 x 182.36 x 146.28
	Weight (Net kg)	2.42
	Weight Without Stand (kg)	2.07
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	56.7 x 12 x 36.5
	Outer Carton Dimension (WxDxH) (cm)	58.7 x 14 x 39.8
	Weight (Gross kg)	3.96
Barcode Info	EAN	4711377429283

“2026-11-20 Changes to the product specifications and errors excepted. The product presentation may differ from the product. Microsoft, Windows, the Windows logo, and DirectX are trademarks or registered trademarks of Microsoft Corporation in the United States and / or other countries. Intel, the Intel logo, Intel Inside, the Intel Inside logo, Intel Core and Core Inside are trademarks of Intel Corporation in the US and other countries. Other trademarks and trade names refer to the respective owners or their products.”