

## Be Your Window To The World



Picture and logos

## SELLING POINTS

- 24.5-inch Broadened Display – Enjoy the upgraded canvas in the limited space.
- The best screen size for the office and work desk aligns with the visual's comfort zone.
- TÜV certified display ensures the protection and health of eyesight.
- MSI EyesErgo technology with Anti-Flicker technology helps prevent eye strain and fatigue.
- 100 Hz refresh rate provides a better viewing experience with flicker-free image.
- MSI Eye-Q Check helps have self-check eyes & reminds to take a rest while using the monitor for a long time.
- Maintain versatility across various devices by utilizing multiple input sources, such as HDMI™, DisplayPort and D-Sub(VGA) ports.
- Enjoy the cleanest environment with a convenient and removable cable management design.
- Standard VESA mountable & Accessory slot design.
- Two built-in speakers.



1. 1x DisplayPort (1.2a)
2. 1x HDMI™ 1.4b (FHD@100Hz)
3. 1x D-Sub (VGA)
4. 1x Line-in
5. 1x DC-in
6. 1x 5-way Navigator
7. 1x Kensington Lock

**SPECIFICATION**

Model	Part No	9S6-3PC7CH-070
	Color	ID1/Black-Black
Display	Screen Size	24.5" (62.23cm)
	Active Display Area (mm)	543.744(H) × 302.616(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	52.28~113.61 KHz (H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	90%/80%
	NTSC (CIE1931 area percentage/overlap)	74%/71%
	sRGB (CIE1976 area percentage/overlap)	103%/97%
	sRGB (CIE1931 area percentage/overlap)	105%/96%
	Adobe RGB (CIE1976 area percentage/overlap)	88%/85%
	Adobe RGB (CIE1931 area percentage/overlap)	78%/74%
	DCI-P3 (CIE1976 area percentage/overlap)	82%/82%
	DCI-P3 (CIE1931 area percentage/overlap)	78%/78%
	Rec.709 (CIE1976 area percentage/overlap)	103%/97%
	Rec.709 (CIE1931 area percentage/overlap)	105%/96%
	Rec.2020 (CIE1976 area percentage/overlap)	60%/60%
	Rec.2020 (CIE1931 area percentage/overlap)	55%/55%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	D-Sub	1
	Line-in	1
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	2
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	External Adaptor 12V 2.5A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	15
	Annual Energy Consumption (KWh)	15
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	D
Power Cord Type	C13	

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	75x75mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	560 x 438.4 x 182.0
	Product Dimension without Stand (WxDxH) (mm)	560 x 331.4 x 53.7
	Stand Dimension (WxDxH) (mm)	178.69 x 237.34 x 182.04
	Weight (Net kg)	3.03
	Weight Without Stand (kg)	2.708
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	63.2 x 12.5 x 41.5
	Outer Carton Dimension (WxDxH) (cm)	64.7 x 14 x 43.7
	Weight (Gross kg)	5.05