

All About Gaming

Inspired by the rigorous quality testing in the production of the MSI Gaming series, the MSI design is full of symbols of sturdiness and durability. Additionally, to provide a quality user experience, the MSI gaming series has a straightforward installation process and a friendly user interface and will be the best choice for entry-level gamers to step into the game world.



Picture and logos

SELLING POINTS

- Rapid IPS – Fornisce un tempo di risposta rapido di 1ms GTG, ottimizza i colori dello schermo e la luminosità.
- 180Hz Refresh Rate – Risponde più velocemente con frame più fluidi.
- Tempo di risposta 1ms GTG – Elimina lo screen tearing e le frequenze di frame irregolari.
- Ampia gamma di colori Gamut – I colori e i dettagli del gioco appariranno più realistici e nitidi.
- Adaptive-sync – Previene lo screen tearing e lo stuttering, dandoti un gameplay ultra-smooth e senza lag.
- Night Vision – Regolazione intelligente del nero per illuminare la tua giornata evidenziando i dettagli fini nelle zone buie.
- Frameless design – Goditi l'esperienza di gioco definitiva con cornici super sottili.
- Anti-Flicker minori emissioni di luce blu – Gioca ancora più a lungo prevenendo l'affaticamento e la stanchezza degli occhi.
- Ampio angolo di visione di 178° – I colori e i dettagli rimarranno nitidi da più angolazioni con un ampio angolo di visione di 178°.



1. 5-way joystick navigator
2. DC-in
3. 1 x Display Port (1.4)
4. 2 x HDMI™ (2.0b)
5. Headphone out
6. Kensington lock



MONITOR

G272QPF E2

G 2 7 2 Q P F E 2

SPECIFICATION

| | | |
|--------------------------------|---|----------------------------|
| Model | SKU Number | 0 |
| | Part No | 9S6-3CD39T-014 |
| | Color | ID1/Black-Black |
| | MKT Name | G272QPF E2 |
| | MKT Spec | G272QPF E2 |
| | Model | 3CD3 |
| Power | Power Type | External Adaptor 20V 2.25A |
| | Power Input | 100~240V, 50/60Hz |
| | On-mode Power Consumption (KWh/1000h) | 26 |
| | Standby-mode Power Consumption (W) | 0.5 |
| | Off-mode Power Consumption (W) | 0.3 |
| | Energy Efficiency Rating | F |
| Design | Power Cord Type | C5 |
| | Adjustment (Tilt) | -5° ~ 20° |
| | Adjustment (Swivel) | -30° ~ 30° |
| | Adjustment (Height) | 0 ~ 130 mm |
| | Adjustment (Pivot) | -90° ~ 90° |
| | VESA Mounting | 100x100mm |
| Dimension & Weight | Frameless Design | Yes |
| | Inside Carton Dimension (WxDxH) (inch) | 33.07 x 5.91 x 18.7 |
| | Weight (Net kg) | 6.3 |
| | Weight (Gross kg) | 8.4 |
| | Product Dimension with Stand (WxDxH) (mm) | 613 x 228 x 409 |
| | Product Dimension with Stand (WxDxH) (inch) | 24.13 x 8.98 x 16.1 |
| Weight | Weight Without Stand (kg) | 3.8 |
| Outer Carton Dimension (WxDxH) | Outer Carton Dimension (WxDxH) (inch) | 33.66 x 6.5 x 19.69 |
| Warranty | Warranty | 36M |
| In The Box | 3.5mm Mic Cable | 0 |
| | Switch Case | 0 |
| | Portable Screen Protection Case | 0 |
| | Monitor Hood | 0 |
| | Speaker (Accessories) | 0 |
| | DisplayPort Cable | 1 |
| | HDMI Cable | 0 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 0 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | Mouse Bungee Unit | 0 |
| | VESA Screw | 4 |
| | Power Cord | 1 |
| | AC Adaptor | 1 |
| | Warranty Card | 0 |
| | Quick Guide | 1 |
| Barcode Info | EAN | 4711377141765 |



MONITOR
G272QPF E2
G 2 7 2 Q P F E 2

| | | |
|------------------------------|--|-----------------------------------|
| Display | Screen Size | 27" (69 cm) |
| | Active Display Area (mm) | 596.736(H) x 335.664(V) |
| | Curvature | Flat |
| | Panel Type | Rapid IPS |
| | Resolution | 2560x1440 (WQHD) |
| | Pixel pitch (mm) | 0.2331(H)x0.2331(V) |
| | HDR (High dynamic range) | HDR Ready |
| | Refresh Rate | 180Hz |
| | Response Time (MPRT) | 1ms(MPRT) |
| | Response Time (GTG) | 5ms |
| | View Angles | 178°(H)/178°(V) |
| | sRGB (CIE1976 area percentage/overlap) | 125%/99% |
| | sRGB (CIE1931 area percentage/overlap) | 127%/100% |
| | Adobe RGB (CIE1976 area percentage/overlap) | 107%/90% |
| | Adobe RGB (CIE1931 area percentage/overlap) | 94%/84% |
| | DCI-P3 (CIE1976 area percentage/overlap) | 99%/94% |
| | DCI-P3 (CIE1931 area percentage/overlap) | 94%/92% |
| | Rec.709 (CIE1976 area percentage/overlap) | 125%/99% |
| | Rec.709 (CIE1931 area percentage/overlap) | 127%/100% |
| | Rec.2020 (CIE1976 area percentage/overlap) | 72%/71% |
| | Rec.2020 (CIE1931 area percentage/overlap) | 67%/67% |
| | Display Colors | 1.07B |
| | Color bit | 10 bits (8 bits + FRC) |
| | Aspect Ratio | 16:9 |
| | Dynamic Refresh Rate technology | Adaptive-Sync |
| | Dynamic Refresh Rate Activated Range | 48~180Hz |
| | SDR Brightness (nits) | 300 |
| | Contrast Ratio | 1200:1 |
| | DCR (Dynamic Contrast Ratio) | 100000000:1 |
| | Signal Frequency | 64.56~266.4 KHz(H) / 48~180 Hz(V) |
| | NTSC (CIE1976 area percentage/overlap) | 109%/86% |
| | NTSC (CIE1931 area percentage/overlap) | 90%/82% |
| | Surface Treatment | Anti-glare |
| Dimension & Weight (box) | Inside Carton Dimension (WxDxH) (cm) | 84 x 15 x 47.5 |
| | Outer Carton Dimension (WxDxH) (cm) | 85.5 x 16.5 x 50 |
| | Weight (Gross kg) | 8.4 |
| I/O Ports | Headphone-out | 1 |
| | Lock type | Kensington Lock |
| | HDMI | 2 |
| | HDMI version | 2.0b |
| | HDMI HDCP version | 2.3 |
| | DisplayPort | 1 |
| | DisplayPort version | 1.4 |
| | DisplayPort HDCP version | 2.3 |
| Dimension & Weight (product) | Product Dimension with Stand (WxDxH) (mm) | 613 x 228 x 409 |
| | Product Dimension without Stand (WxDxH) (mm) | 613 x 61 x 369 |
| | Stand Dimension (WxDxH) (mm) | 309 x 228 x 391 |
| | Weight (Net kg) | 6.3 |
| | Weight Without Stand (kg) | 3.8 |