


PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- Pannello Rapid IPS – Offre un tempo di risposta di 0,5 ms (GtG, Min.) e ottimizza i colori e la luminosità dello schermo.
- Refresh rate di 200 Hz – Reagisci più rapidamente grazie a immagini ancora più fluide.
- Tempo di risposta di 0,5 ms (GtG, Min.) – Riduce il tearing dello schermo e le immagini poco fluide.
- AI Vision – La nuova tecnologia AI Vision migliora la visibilità dei dettagli nelle aree scure, ottimizzando al contempo la luminosità generale e la saturazione dei colori.
- Less Blue Light – Una soluzione software che riduce l'emissione luminosa nella regione blu-viola dello spettro della luce blu.



1. 5-Way Navi Key
2. AC-in
3. 2x HDMI™ 2.0b (FHD@200Hz)
4. DisplayPort 1.2a
5. Headphone-out
6. Kensington Lock



MONITOR

MAG 256F E20

MAG 256FA E20

SPECIFICATION

Model	SKU Number	9S6-3BC2CM-083
	Entity MKT Name	MAG 256FA E20
	Part No	9S6-3BC2CM-083
	Color	ID1/Black-Black
Display	Screen Size	24.5" (62.23cm)
	Active Display Area (mm)	543.744(H) x 302.616(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.8~220 KHz(H) / 48~200 Hz(V)
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	86%/78%
	NTSC (CIE1931 area percentage/overlap)	73%/71%
	sRGB (CIE1976 area percentage/overlap)	99%/95%
	sRGB (CIE1931 area percentage/overlap)	104%/96%
	Adobe RGB (CIE1976 area percentage/overlap)	84%/83%
	Adobe RGB (CIE1931 area percentage/overlap)	77%/74%
	DCI-P3 (CIE1976 area percentage/overlap)	78%/78%
	DCI-P3 (CIE1931 area percentage/overlap)	76%/76%
	Rec.709 (CIE1976 area percentage/overlap)	99%/95%
	Rec.709 (CIE1931 area percentage/overlap)	104%/96%
	Rec.2020 (CIE1976 area percentage/overlap)	57%/57%
	Rec.2020 (CIE1931 area percentage/overlap)	54%/54%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13



MONITOR

MAG 256F E20

MAG 256FA E20

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	557.09 x 205.98 x 423.61
	Product Dimension without Stand (WxDxH) (mm)	557.09 x 64.36 x 326.85
	Stand Dimension (WxDxH) (mm)	227.81 x 207.23 x 146.28
	Weight (Net kg)	3.25
	Weight Without Stand (kg)	2.83
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	63 x 12.5 x 40.4
	Outer Carton Dimension (WxDxH) (cm)	65 x 14.5 x 43.6
	Weight (Gross kg)	4.75
Barcode Info	EAN	4711377398015