

## PATH TO THE FUTURE

Presentiamo il monitor da gaming esports MSI MAG 274CXF. Questo monitor all'avanguardia presenta un display FHD da 27 pollici con una velocissima frequenza di aggiornamento di 280Hz e un rapido tempo di risposta di 0.5ms (GtG, Min.). Con il MAG 274CXF, avrai il vantaggio competitivo necessario per superare e sconfiggere i tuoi avversari nelle battaglie di gaming.



Picture and logos

## SELLING POINTS

- Pannello Rapid VA - Offre un tempo di risposta di 0.5ms (GtG, Min.), ottimizzando colori e luminosità dello schermo.
- Refresh Rate a 280Hz - Reagisci più velocemente con immagini più fluide.
- Tempo di Risposta di 0.5ms (GtG, Min.) - Elimina screen tearing e frame rate scattosi.
- AI Vision - La nuova tecnologia AI Vision non solo rivela i dettagli nelle aree scure, ma migliora anche la luminosità generale e la saturazione dei colori.
- Less Blue Light - Utilizza una soluzione software per ridurre l'emissione di luce nella regione blu-viola dello spettro della luce blu.



1. 5-way Joystick Navigator
2. DC-in
3. Display Port 1.2a
4. 2x HDMI™ 2.0b(FHD@240Hz)
5. Earphone out
6. Kensington Lock

## SPECIFICATION

Model	Part No	9S6-3CE31T-017
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~280Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	4000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	309.504~589.120 KHz(H) / 48~280 Hz(V)
	Refresh Rate	280Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	107.5%/83.3%
	NTSC (CIE1931 area percentage/overlap)	85.2%/77%
	sRGB (CIE1976 area percentage/overlap)	123.3%/99.1%
	sRGB (CIE1931 area percentage/overlap)	120.3%/99.7%
	Adobe RGB (CIE1976 area percentage/overlap)	105.7%/88.3%
	Adobe RGB (CIE1931 area percentage/overlap)	89.1%/81.5%
	DCI-P3 (CIE1976 area percentage/overlap)	98.2%/92.2%
	DCI-P3 (CIE1931 area percentage/overlap)	88.7%/86.7%
	Rec.709 (CIE1976 area percentage/overlap)	123.3%/99.1%
	Rec.709 (CIE1931 area percentage/overlap)	120.3%/99.7%
	Rec.2020 (CIE1976 area percentage/overlap)	71.5%/71.5%
	Rec.2020 (CIE1931 area percentage/overlap)	63.6%/63.6%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	External Adaptor 20V 2.25A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C5	

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	614 x 250 x 438
	Product Dimension without Stand (WxDxH) (mm)	614 x 77 x 364
	Stand Dimension (WxDxH) (mm)	340 x 250 x 140
	Weight (Net kg)	3.4
	Weight Without Stand (kg)	3.0
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	75 x 15 x 48.8
	Outer Carton Dimension (WxDxH) (cm)	76.5 x 16.5 x 51.5
	Weight (Gross kg)	6.1
Barcode Info	EAN	4711377331579