

## PATH TO THE FUTURE

The MAG 274QPF X30MV Gaming Monitor with 27 inch of Rapid VA and Mini-LED (1152 Zones), 2560x1440 WQHD and 300Hz, and DisplayHDR 1000 for ultra-smooth visuals. Unleash your full potential.



Picture and logos

## SELLING POINTS

- Mini-LED – Migliora l'HDR grazie al local dimming a matrice completa e 1.152 zone per neri più profondi e luci più intense.
- Rapid VA – Garantisce intensità e purezza dei colori durante il gioco.
- VESA DisplayHDR 1000 – Dettagli sorprendenti certificati VESA, grazie a un contrasto preciso e alla regolazione delle ombre.
- Refresh Rate a 300Hz – Offre immagini fluide per una risposta più rapida nei giochi.
- Tempo di risposta di 0,5ms (GtG, min.) – Elimina tearing e rallentamenti dell'immagine.
- Console Mode – Ottimizzato per una perfetta compatibilità con console come PS5 e Xbox Series X|S.
- Tecnologia Quantum Dot – Oltre un miliardo di colori vivaci con una chiarezza straordinaria.
- Opzioni di formato – Scegli tra diversi formati per un'esperienza di gioco più personalizzata.



1. 2x HDMI™ 2.1 (WQHD@300Hz)
2. 5-Way Navigator
3. DisplayPort 1.4a (HBR3)
4. Headphone-out
5. DC-in
6. Kensington Lock



MONITOR

MAG 274QPF X30MV

M A G 2 7 4 Q P F X 3 0 M V

## SPECIFICATION

|           |   |                                    |
|-----------|---|------------------------------------|
| Model     | SKU Number                                  | 9S6-3CF09H-001                     |
|           | Entity MKT Name                             | MAG 274QPF X30MV                   |
|           | Part No                                     | 9S6-3CF09H-001                     |
|           | Color                                       | ID1/Black-Black                    |
|           | Local Dimming                               | 1152 Zones                         |
| Display   | Screen Size                                 | 27" (68.58 cm)                     |
|           | Active Display Area (mm)                    | 596.736(H) x 335.664(V)            |
|           | Curvature                                   | Flat                               |
|           | Panel Type                                  | Rapid VA Mini-LED                  |
|           | Resolution                                  | 2560x1440 (WQHD)                   |
|           | Pixel pitch (mm)                            | 0.2331(H)x0.2331(V)                |
|           | Aspect Ratio                                | 16:9                               |
|           | Dynamic Refresh Rate technology             | Adaptive-Sync                      |
|           | Dynamic Refresh Rate Activated Range        | 48~300Hz                           |
|           | HDR (High dynamic range)                    | VESA DisplayHDR 1000               |
|           | SDR Brightness (nits)                       | 400                                |
|           | HDR Brightness (Peak nits)                  | 1000                               |
|           | Contrast Ratio                              | 4500:1                             |
|           | DCR (Dynamic Contrast Ratio)                | 100000000:1                        |
|           | Signal Frequency                            | 88.56~432.14 KHz(H) / 48~300 Hz(V) |
|           | Refresh Rate                                | 300Hz                              |
|           | Response Time (MPRT)                        | 1ms(MPRT)                          |
|           | Response Time (GTG)                         | 0.5ms (Min.)                       |
|           | View Angles                                 | 178°(H)/178°(V)                    |
|           | NTSC (CIE1976 area percentage/overlap)      | 133%/95%                           |
|           | NTSC (CIE1931 area percentage/overlap)      | 109%/93%                           |
|           | SRGB (CIE1976 area percentage/overlap)      | 152%/100%                          |
|           | SRGB (CIE1931 area percentage/overlap)      | 154%/100%                          |
| I/O Ports | Adobe RGB (CIE1976 area percentage/overlap) | 129%/99%                           |
|           | Adobe RGB (CIE1931 area percentage/overlap) | 114%/97%                           |
|           | DCI-P3 (CIE1976 area percentage/overlap)    | 120%/97%                           |
|           | DCI-P3 (CIE1931 area percentage/overlap)    | 114%/92%                           |
|           | Rec.709 (CIE1976 area percentage/overlap)   | 152%/100%                          |
|           | Rec.709 (CIE1931 area percentage/overlap)   | 154%/100%                          |
|           | Rec.2020 (CIE1976 area percentage/overlap)  | 87%/87%                            |
|           | Rec.2020 (CIE1931 area percentage/overlap)  | 83%/83%                            |
|           | Surface Treatment                           | Anti-glare                         |
|           | Display Colors                              | 1.07B                              |
| Warranty  | Color bit                                   | 10 bits (8 bits + FRC)             |
|           | Headphone-out                               | 1                                  |
|           | Lock type                                   | Kensington Lock                    |
|           | HDMI  | 2                                  |
|           | HDMI version                                | 2.1 (FRL 6G)                       |
|           | HDMI HDCP version                           | 2.3                                |
|           | DisplayPort                                 | 1                                  |
|           | DisplayPort version                         | 1.4a                               |
|           | DisplayPort HDCP version                    | 2.3                                |
| Power     | Warranty                                    | 36M                                |
|           | Power Type                                  | External Adaptor 19V 5.79A         |
|           | Power Input                                 | 100~240V, 50/60Hz                  |
|           | On-mode Power Consumption (KWh/1000h)       | 26                                 |
|           | Annual Energy Consumption (KWh)             | 26                                 |
|           | Standby-mode Power Consumption (W)          | 0.5                                |
|           | Off-mode Power Consumption (W)              | 0.3                                |
|           | Energy Efficiency Rating                    | F                                  |
|           | Power Cord Type                             | C5                                 |



MONITOR

MAG 274QPF X30MV

MAG 274QPF X30MV

|                              |  |                          |
|------------------------------|--|--------------------------|
| In The Box                   | DisplayPort Cable                            | 1                        |
|                              | HDMI Cable                                   | 0                        |
|                              | DVI Cable                                    | 0                        |
|                              | USB Type A to Type B Cable                   | 0                        |
|                              | USB Type C to Type A Cable                   | 0                        |
|                              | USB Type C to Type C Cable                   | 0                        |
|                              | Thunderbolt Cable                            | 0                        |
|                              | VGA Cable                                    | 0                        |
|                              | 3.5mm audio Cable                            | 0                        |
|                              | 3.5mm combo audio Cable                      | 0                        |
|                              | 3.5mm Mic Cable                              | 0                        |
|                              | Power Cord                                   | 1                        |
|                              | AC Adaptor                                   | 1                        |
|                              | Quick Guide                                  | 1                        |
|                              | Warranty Card                                | 0                        |
|                              | Mouse Bungee Unit                            | 0                        |
|                              |  |                          |
| Design                       | Adjustment (Tilt)                            | -5° ~ 20°                |
|                              | Adjustment (Swivel)                          | -30° ~ 30°               |
|                              | Adjustment (Height)                          | 0 ~ 110 mm               |
|                              | Adjustment (Pivot)                           | -90° ~ 90°               |
|                              | VESA Mounting                                | 100x100mm                |
| Dimension & Weight (product) | Product Dimension with Stand (WxDxH) (mm)    | 613.10 x 227.90 x 423.53 |
|                              | Product Dimension without Stand (WxDxH) (mm) | 613.10 x 68.77 x 375.31  |
|                              | Stand Dimension (WxDxH) (mm)                 | 312.53 x 202.38 x 402.73 |
|                              | Weight (Net kg)                              | 7.5                      |
|                              | Weight Without Stand (kg)                    | 4.5                      |
| Dimension & Weight (box)     | Inside Carton Dimension (WxDxH) (cm)         | 91 x 17 x 47             |
|                              | Outer Carton Dimension (WxDxH) (cm)          | 92.5 x 18.3 x 49.4       |
|                              | Weight (Gross kg)                            | 11.                      |
| Barcode Info                 | EAN  | 4711377298919            |