

PATH TO THE FUTURE

Introducing the MSI MAG 274CXF esports gaming monitor. This cutting-edge monitor features a 27-inch FHD display with a lightning-fast 280Hz refresh rate and a rapid 0.5ms (GtG, Min.) response time. With the MAG 274CXF, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

SELLING POINTS

- Pannello Rapid VA - Offre un tempo di risposta di 0,5 ms (GtG, Min.), ottimizza i colori e la luminosità dello schermo.
- Refresh Rate a 180Hz - Rispondi più rapidamente con immagini più fluide.
- Tempo di risposta di 0,5 ms (GtG, Min.) - Elimina tearing e fotogrammi a scatti.
- AI Vision - La nuova tecnologia AI Vision non solo rivela i dettagli nelle aree scure, ma migliora anche la luminosità complessiva e la saturazione dei colori.
- Meno luce blu - Utilizza una soluzione software per ridurre l'emissione nella regione blu-viola dello spettro della luce blu.



1. 5-Way Navigator
2. DC-in
3. Headphone-out
4. DisplayPort 1.4a
5. 2x HDMI™ 2.0b (WQHD@144Hz)
6. Type-C
7. Kensington Lock

SPECIFICATION

Model	Part No	9S6-3DC11H-089
	Color	ID1/Black-Black
Display	Screen Size	31.5" (80.01 cm)
	Active Display Area (mm)	697.344 (H) x 392.256 (V)
	Curvature	Curve 1000R
	Panel Type	Rapid VA
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2724(H)x0.2724(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	3500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	90.90~248.25 KHz(H) / 48~180 Hz(V)
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	108%/87%
	NTSC (CIE1931 area percentage/overlap)	90%/82%
	sRGB (CIE1976 area percentage/overlap)	124%/99%
	sRGB (CIE1931 area percentage/overlap)	128%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	106%/91%
	Adobe RGB (CIE1931 area percentage/overlap)	95%/86%
	DCI-P3 (CIE1976 area percentage/overlap)	99%/96%
	DCI-P3 (CIE1931 area percentage/overlap)	94%/92%
	Rec.709 (CIE1976 area percentage/overlap)	124%/99%
	Rec.709 (CIE1931 area percentage/overlap)	128%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	72%/72%
	Rec.2020 (CIE1931 area percentage/overlap)	67%/67%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
I/O Ports	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	External Adaptor 19V 4.74A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	32
	Annual Energy Consumption (KWh)	32
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C5	



MONITOR
MAG 325CQF
MAG 325CQF

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	704.62 x 269.46 x 502.85
	Product Dimension without Stand (WxDxH) (mm)	704.62 x 143.45 x 422.35
	Stand Dimension (WxDxH) (mm)	379.66 x 269.46 x 142.52
	Weight (Net kg)	6.4
	Weight Without Stand (kg)	5.65
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	80.8 x 19.6 x 51.6
	Outer Carton Dimension (WxDxH) (cm)	82.3 x 21.1 x 54
	Weight (Gross kg)	8.6
Barcode Info	EAN	4711377332019