

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- Pannello QD-OLED di terza generazione - Con qualità dell'immagine straordinaria e tempi di risposta rapidi.
- Tempo di risposta GtG di 0,03 ms e frequenza di aggiornamento di 240 Hz.
- QD Premium Color - Garantisce che il colore soddisfi lo standard di mercato - Delta E≤2.
- Incredibile visuale HDR - VESA DisplayHDR True Black 400.
- App Gaming Intelligence - Crea le impostazioni di visualizzazione perfette per i tuoi giochi.
- MSI OLED Care 2.0 - Riduce il rischio di bruciature dell'immagine OLED.
- KVM - Controlla più dispositivi tramite una sola tastiera, mouse e monitor.
- Modalità console - Fornisce HDMI™ 2.1 (UHD@240Hz) con una larghezza di banda completa di 48 Gbps.
- Garanzia di 3 anni contro il burn-in - Inclusa la copertura per il burn-in dell'OLED.



1. 2x HDMI™ 2.1 (UHD@240Hz)
2. 1x DisplayPort 1.4a
3. 1x Type-C (DP alt.) w/ 98W PD
4. 2x USB 2.0 Type-A
5. 1x USB 2.0 Type-B
6. Headphone-out
7. 5-Way Navigator
8. AC-in
9. Kensington Lock



MONITOR

MPG 321CURX QD-OLED

MPG 321CURX QD-OLED

SPECIFICATION

Model	Part No	9S6-3DD64T-001
	Color	ID1/Black-Black
Display	Screen Size	31.5" (80 cm)
	Active Display Area (mm)	699.48(H) x 394.73(V)
	Curvature	Curve 1700R
	Panel Type	QD-OLED
	Resolution	3840x2160 (UHD)
	Pixel pitch (mm)	0.1814(H)x0.1814(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	True Black 400
	SDR Brightness (nits)	250
	HDR Brightness (Peak nits)	1000
	Contrast Ratio	1500000:1
	Signal Frequency	30~566 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	120.5%/93.8%
	NTSC (CIE1931 area percentage/overlap)	103.6%/91.5%
	SRGB (CIE1976 area percentage/overlap)	138.2%/100%
	SRGB (CIE1931 area percentage/overlap)	146.2%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	118.4%/97.5%
	Adobe RGB (CIE1931 area percentage/overlap)	108.4%/94%
	DCI-P3 (CIE1976 area percentage/overlap)	110.1%/99%
	DCI-P3 (CIE1931 area percentage/overlap)	107.8%/98.4%
	Rec.709 (CIE1976 area percentage/overlap)	138.2%/100%
	Rec.709 (CIE1931 area percentage/overlap)	146.2%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80.2%/80.2%
	Rec.2020 (CIE1931 area percentage/overlap)	77.3%/77.3%
	Surface Treatment	Anti-Reflection
	Display Colors	1.07B
	Color bit	10 bits
I/O Ports	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	USB 2.0 Type A	2
	USB 2.0 Type B	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.1
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	N/A
	Power Cord Type	C13



MONITOR

MPG 321CURX QD-OLED

MPG 321CURX QD-OLED

In The Box	DisplayPort Cable	1
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
	Adjustment (Tilt)	-5° ~ 20°
Design	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 100 mm
	VESA Mounting	100x100mm
	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
Dimension & Weight (product)	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	TBD
	Weight Without Stand (kg)	TBD
	Inside Carton Dimension (WxDxH) (cm)	N/A
Dimension & Weight (box)	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	TBD
Barcode Info	EAN	4711377250719