

PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- L'ultimo pannello QD-OLED di 4a generazione - Offre una qualità d'immagine straordinaria e tempi di risposta rapidissimi.
- Pannello OLED tandem a 5 strati con tecnologia EL Gen 3 - Efficienza luminosa fino al 30%.
- DarkArmor Film - Garantisce neri del 40% più profondi e una superficie dello schermo 2,5 volte più resistente ai graffi.
- Uniform Luminance - Personalizzazione della curva HDR per regolare la resa dell'HDR e godere di un'esperienza HDR uniforme e fluida.
- MSI OLED Care 3.0 - Il sensore AI Care riduce il rischio di image sticking / burn-in del pannello OLED.
- Immagini HDR straordinarie - Certificazione VESA DisplayHDR True Black 500.
- Picco di luminosità di 1000 nit - Per un'esperienza HDR superiore con una luminosità di picco fino a 1000 nit.
- Colori conformi agli standard di mercato - Delta E ≤ 2.
- Movimenti estremamente nitidi - Certificazione VESA ClearMR 13000.
- Garanzia di 3 anni contro il burn-in - Include la copertura per il burn-in del pannello OLED.



1. AC-in
2. 5-way Joystick Navigator
3. 2x HDMI™ 2.1 (UHD@240Hz)
4. DisplayPort 2.1a (UHBR20)
5. USB Type-C (98W PD)
6. USB Type-B
7. 2x USB Type-A
8. Headphone-out
9. Kensington lock

SPECIFICATION

| | | |
|-----------------|---|--|
| Model | SKU Number | 9S6-3DD39T-038 |
| | Entity MKT Name | MPG 322UR QD-OLED X24 |
| | Part No | 9S6-3DD39T-038 |
| | Color | ID1/Black-Black |
| Display | Screen Size | 31.5" (80.01 cm) |
| | Active Display Area (mm) | 699.48(H) x 394.73(V) |
| | Curvature | Flat |
| | Panel Type | QD-OLED |
| | Resolution | 3840x2160 (UHD) |
| | Pixel pitch (mm) | 0.1814(H)x0.1814(V) |
| | Aspect Ratio | 16:9 |
| | Dynamic Refresh Rate technology | NVIDIA G-SYNC Compatible / AMD FreeSync™ Premium Pro |
| | Dynamic Refresh Rate Activated Range | 48~240Hz |
| | HDR (High dynamic range) | VESA DisplayHDR True Black 500 |
| | SDR Brightness (nits) | 300 |
| | HDR Brightness (Peak nits) | 1000 |
| | Contrast Ratio | 1500000:1 |
| | Signal Frequency | 560.6~562.6 KHz(H) / 48~240 Hz(V) |
| | Refresh Rate | 240HZ |
| | Response Time (GTG) | 0.03ms |
| | View Angles | 178°(H)/178°(V) |
| | NTSC (CIE1976 area percentage/overlap) | 121%/93% |
| | NTSC (CIE1931 area percentage/overlap) | 105%/91% |
| | sRGB (CIE1976 area percentage/overlap) | 138%/100% |
| | sRGB (CIE1931 area percentage/overlap) | 149%/100% |
| | Adobe RGB (CIE1976 area percentage/overlap) | 119%/97% |
| | Adobe RGB (CIE1931 area percentage/overlap) | 110%/94% |
| | DCI-P3 (CIE1976 area percentage/overlap) | 110%/99% |
| | DCI-P3 (CIE1931 area percentage/overlap) | 109%/99% |
| | Rec.709 (CIE1976 area percentage/overlap) | 138%/100% |
| | Rec.709 (CIE1931 area percentage/overlap) | 149%/100% |
| | Rec.2020 (CIE1976 area percentage/overlap) | 80%/80% |
| | Rec.2020 (CIE1931 area percentage/overlap) | 79%/79% |
| | Surface Treatment | Anti-Reflection |
| | Display Colors | 1.07B |
| Color bit | 10 bits | |
| I/O Ports | USB Type C (DisplayPort Alternate) | 1 |
| | Headphone-out | 1 |
| | USB 3.2 Gen 1 Type A | 2 |
| | USB 3.2 Gen 1 Type B | 1 |
| | Lock type | Kensington Lock |
| | HDMI | 2 |
| | HDMI version | 2.1 |
| | HDMI HDCP version | 2.3 |
| | DisplayPort | 1 |
| | DisplayPort version | 2.1a (UHBR20) |
| | DisplayPort HDCP version | 2.3 |
| Warranty | Warranty | 36M |
| Power | Power Type | Internal Power Board |
| | Power Input | 100~240V, 50/60Hz |
| | On-mode Power Consumption (KWh/1000h) | 32 (SDR) 38 (HDR) |
| | Annual Energy Consumption (KWh) | 44 |
| | Standby-mode Power Consumption (W) | 0.5 |
| | Off-mode Power Consumption (W) | 0.3 |
| | Energy Efficiency Rating | F (SDR) G (HDR) |
| Power Cord Type | C13 | |

| | | |
|------------------------------|--|-----------------------|
| In The Box | DisplayPort Cable | 1 |
| | HDMI Cable | 1 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 1 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 1 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | 3.5mm Mic Cable | 0 |
| | Power Cord | 1 |
| | AC Adaptor | 0 |
| | Quick Guide | 1 |
| | Warranty Card | 0 |
| Mouse Bungee Unit | 0 | |
| Design | Adjustment (Tilt) | -5° ~ 15° |
| | Adjustment (Swivel) | -30° ~ 30° |
| | Adjustment (Height) | 0 ~ 110 mm |
| | Adjustment (Pivot) | -10° ~ 10° |
| | VESA Mounting | 100x100mm |
| Dimension & Weight (product) | Product Dimension with Stand (WxDxH) (mm) | 717.3 x 241.9 x 477.1 |
| | Product Dimension without Stand (WxDxH) (mm) | 717.3 x 71.8 x 434.8 |
| | Stand Dimension (WxDxH) (mm) | 308.7 x 241.9 x 390.8 |
| | Weight (Net kg) | 9.4 |
| | Weight Without Stand (kg) | 6.6 |
| Dimension & Weight (box) | Inside Carton Dimension (WxDxH) (cm) | 98.5 x 16.9 x 51.3 |
| | Outer Carton Dimension (WxDxH) (cm) | 100 x 18.4 x 53.6 |
| | Weight (Gross kg) | 14.8 |
| Barcode Info | EAN | 4711377409179 |