

Be Your Window To The World



Picture and logos

SELLING POINTS

- Dimensione dello schermo da 21,45" perfetta per attività di programmazione, coding e web design.
- Display certificato TÜV per garantire la protezione e la salute della vista.
- La tecnologia MSI EyesErgo con Anti-Flicker aiuta a prevenire affaticamento e stanchezza degli occhi.
- La frequenza di aggiornamento a 100 Hz offre un'esperienza visiva migliore con immagini prive di sfarfallio.
- MSI Eye-Q Check consente di effettuare un'autovalutazione della vista e ricorda di fare delle pause durante l'uso prolungato del monitor.
- Mantieni la massima versatilità con diversi dispositivi grazie a più sorgenti di ingresso, come HDMI™ e D-Sub (VGA).
- Goditi una postazione più ordinata grazie al pratico sistema di gestione dei cavi, comodo e rimovibile.
- Compatibile con montaggio VESA standard e dotato di slot per accessori.



1. 1x 5-way navigator
2. 1x AC-in
3. 1x HDMI™ (1.4b)
4. 1x D-Sub (VGA)
5. 1x Kensington Lock

SPECIFICATION

Model	Part No	9S6-3PE0CM-001
	Color	ID1/Black-Black
Display	Screen Size	21.45" (54.483 cm)
	Active Display Area (mm)	478.656 (H) x 260.28 (V)
	Curvature	Flat
	Panel Type	N/A
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2493(H)x0.241(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	300
	HDR Brightness (Peak nits)	530
	Contrast Ratio	4000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	N/A
	Refresh Rate	100HZ
	Response Time (MPRT)	N/A
	Response Time (GTG)	14ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	N/A
	NTSC (CIE1931 area percentage/overlap)	N/A
	sRGB (CIE1976 area percentage/overlap)	N/A
	sRGB (CIE1931 area percentage/overlap)	N/A
	Adobe RGB (CIE1976 area percentage/overlap)	N/A
	Adobe RGB (CIE1931 area percentage/overlap)	N/A
	DCI-P3 (CIE1976 area percentage/overlap)	N/A
	DCI-P3 (CIE1931 area percentage/overlap)	N/A
	Rec.709 (CIE1976 area percentage/overlap)	N/A
	Rec.709 (CIE1931 area percentage/overlap)	N/A
	Rec.2020 (CIE1976 area percentage/overlap)	N/A
	Rec.2020 (CIE1931 area percentage/overlap)	N/A
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	

I/O Ports	Thunderbolt	N/A
	Thunderbolt version	N/A
	Thunderbolt HDCP version	N/A
	USB Type C (DisplayPort Alternate)	N/A
	DVI	N/A
	D-Sub	N/A
	Line-in	N/A
	Mic-in	N/A
	Mic-in upstream	N/A
	Headphone-out	N/A
	Audio Combo	N/A
	USB 2.0 Type A	N/A
	USB 2.0 Type B	N/A
	USB 2.0 Type C	N/A
	USB 3.2 Gen 1 Type A	N/A
	USB 3.2 Gen 1 Type B	N/A
	USB 3.2 Gen 1 Type C	N/A
	USB 3.2 Gen 2x2 Type C	N/A
	USB 3.2 Gen 2x2 Type A	N/A
	Card reader	N/A
	Lock type	N/A
	Speaker	N/A
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	N/A
	DisplayPort version	N/A
DisplayPort HDCP version	N/A	
Warranty	Warranty	24M
Power	Power Type	N/A
	Power Input	N/A
	On-mode Power Consumption (KWh/1000h)	N/A
	Annual Energy Consumption (KWh)	N/A
	Standby-mode Power Consumption (W)	N/A
	Off-mode Power Consumption (W)	N/A
	Energy Efficiency Rating	N/A
Power Cord Type	N/A	
In The Box	DisplayPort Cable	N/A
	HDMI Cable	1
	DVI Cable	N/A
	USB Type A to Type B Cable	N/A
	USB Type C to Type A Cable	N/A
	USB Type C to Type C Cable	N/A
	Thunderbolt Cable	N/A
	VGA Cable	N/A
	3.5mm audio Cable	N/A
	3.5mm combo audio Cable	N/A
	3.5mm Mic Cable	N/A
	Power Cord	N/A
	AC Adaptor	N/A
	Quick Guide	N/A
	Warranty Card	N/A
Mouse Bungee Unit	N/A	
Design	Adjustment (Tilt)	N/A
	Adjustment (Swivel)	N/A
	Adjustment (Height)	N/A
	Adjustment (Pivot)	N/A
	VESA Mounting	N/A



PRO MP225V

PRO MP225V

Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	N/A
Barcode Info	EAN	4711377261142