

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- Goditi un intrattenimento di alta qualità con una frequenza di aggiornamento di 100Hz per un'esperienza più fluida.
- Il display certificato TÜV garantisce la protezione e la salute degli occhi.
- La tecnologia MSI EyesErgo con tecnologia Anti-Flicker aiuta a prevenire affaticamento e tensione degli occhi.
- MSI Eye-Q Check ti aiuta a fare un'autocontrollo degli occhi e ti ricorda di fare una pausa quando usi il monitor per lungo tempo.
- Mantieni la versatilità su diversi dispositivi utilizzando fonti di ingresso multiple, come HDMI™ e DisplayPort.
- Goditi un ambiente più pulito con un design conveniente e rimovibile per la gestione dei cavi.
- La tecnologia HDR produce immagini con maggiori dettagli.



1. 5-way Navigator
2. 1x DC Jack
3. 1x Headphone-out
4. 1x DisplayPort 1.2a
5. 1x HDMI™ 1.4b (FHD@100Hz)
6. Kensington Lock



SPECIFICATION

Model	Part No	9S6-3PD5CT-015
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04(H) x 296.46(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	52.8~110 KHz(H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	91%/79%
	NTSC (CIE1931 area percentage/overlap)	72%/69%
	sRGB (CIE1976 area percentage/overlap)	104%/97%
	sRGB (CIE1931 area percentage/overlap)	102%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	89%/85%
	Adobe RGB (CIE1931 area percentage/overlap)	76%/73%
	DCI-P3 (CIE1976 area percentage/overlap)	83%/83%
	DCI-P3 (CIE1931 area percentage/overlap)	75%/75%
	Rec.709 (CIE1976 area percentage/overlap)	104%/97%
	Rec.709 (CIE1931 area percentage/overlap)	102%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	60%/60%
	Rec.2020 (CIE1931 area percentage/overlap)	54%/54%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Warranty	Warranty	24M
Power	Power Type	External Adaptor 12V 2A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	14 (SDR) 30 (HDR)
	Annual Energy Consumption (KWh)	27
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	D (SDR) G (HDR)



PRO MP242L

PRO MP242L

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	0
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-3.5° ~ 21.5°
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	542 x 174 x 391
	Product Dimension without Stand (WxDxH) (mm)	542 x 28 x 321
	Stand Dimension (WxDxH) (mm)	174 x 174 x 111
	Weight (Net kg)	1.8
	Weight Without Stand (kg)	1.6
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	60 x 11.1 x 40
	Outer Carton Dimension (WxDxH) (cm)	61.5 x 12.6 x 42.3
	Weight (Gross kg)	3.3
Barcode Info	EAN	4711377258968