

Slim, Sleek, Smooth



Picture and logos

SELLING POINTS

- PerfectEdge - il design con cornici sottili su 4 lati consente un'immersione totale in configurazioni multi-display.
- Goditi contenuti di alta qualità con maggiore fluidità grazie al refresh rate elevato di 144Hz.
- Il display certificato TÜV garantisce protezione e benessere per la vista.
- La tecnologia MSI EyesErgo con Anti-Flicker aiuta a prevenire affaticamento visivo e stanchezza.
- MSI Eye-Q Check consente di monitorare la salute degli occhi e ricorda di fare pause durante un utilizzo prolungato del monitor.
- Il supporto è progettato con caratteristiche ergonomiche, tra cui regolazione di inclinazione, rotazione, altezza e pivot.
- Il supporto regolabile con design compatibile con il montaggio di un mini PC offre una postazione più ergonomica e ordinata, migliorando comfort e organizzazione.
- Massima versatilità tra diversi dispositivi grazie a molteplici ingressi, tra cui porte HDMI™, DisplayPort e D-Sub (VGA).
- Compatibile con montaggio VESA standard e dotato di Accessory Slot.
- Due speaker integrati.



1. 5-way Navigator
2. AC-in
3. 1x DisplayPort 1.4a
4. 1x HDMI™ 2.0 (FHD@144Hz)
5. 1x D-Sub (VGA)
6. 1x Line-in
7. 1x Headphone-out
8. Kensington Lock

SPECIFICATION

Model	Part No	9S6-3PE39M-001
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04(H) x 296.46(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	52.85~158.54 KHz(H) / 48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	93%/82%
	NTSC (CIE1931 area percentage/overlap)	76%/71%
	sRGB (CIE1976 area percentage/overlap)	107%/95%
	sRGB (CIE1931 area percentage/overlap)	108%/97%
	Adobe RGB (CIE1976 area percentage/overlap)	91%/85%
	Adobe RGB (CIE1931 area percentage/overlap)	79%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	85%/84%
	DCI-P3 (CIE1931 area percentage/overlap)	79%/79%
	Rec.709 (CIE1976 area percentage/overlap)	107%/95%
	Rec.709 (CIE1931 area percentage/overlap)	108%/97%
	Rec.2020 (CIE1976 area percentage/overlap)	61%/61%
	Rec.2020 (CIE1931 area percentage/overlap)	56%/56%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	D-Sub	1
	Line-in	1
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	1
	HDMI version	2.0
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	539.36 x 226.93 x 519.29
	Product Dimension without Stand (WxDxH) (mm)	539.36 x 51.71 x 314.67
	Stand Dimension (WxDxH) (mm)	259.73 x 226.93 x 422.55
	Weight (Net kg)	5.25
	Weight Without Stand (kg)	2.7
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	60 x 12.5 x 50
	Outer Carton Dimension (WxDxH) (cm)	62 x 14.5 x 52.8
	Weight (Gross kg)	7.51
Barcode Info	EAN	4711377318334