

Business & Productivity Monitor



Picture and logos

SELLING POINTS

- Webcam FHD integrata con microfono digitale e copertura per webcam
- Display certificato TÜV che garantisce la protezione e la salute della vista.
- La tecnologia MSI EyesErgo con tecnologia Anti-Flicker aiuta a prevenire l'affaticamento e il disturbo agli occhi.
- La frequenza di aggiornamento di 120 Hz offre una migliore esperienza visiva con immagini senza sfarfallio.
- MSI Eye-Q Check aiuta a fare un auto-controllo degli occhi e ricorda di fare delle pause durante l'uso prolungato del monitor.
- Il supporto è progettato con caratteristiche ergonomiche, inclusi regolazioni di inclinazione, rotazione, altezza e pivot.
- Un supporto regolabile con design montabile per mini-PC offre una configurazione più ergonomica e ordinata, migliorando il comfort e l'organizzazione dell'utente.
- Design supporto VESA standard e fessura per accessori.
- Due altoparlanti integrati.



1. 5-way Navigator
2. AC-in
3. 1x Headphone-out
4. 1x DisplayPort 1.2a
5. 1x HDMI™ 1.4b (FHD@120Hz)
6. 1x D-Sub (VGA)
7. 2x USB 2.0 Type-A
8. 1x USB 2.0 Type-B
9. Kensington Lock

SPECIFICATION

Model	SKU Number	9S6-3PD99T-001	
	Entity MKT Name	PRO MP272PMG	
	Part No	9S6-3PD99T-001	
	Color	ID1/Black-Black	
Display	Screen Size	27" (68.58 cm)	
	Active Display Area (mm)	597.888 (H) x 336.312 (V)	
	Curvature	Flat	
	Panel Type	IPS	
	Resolution	1920x1080 (FHD)	
	Pixel pitch (mm)	0.3114(H)x0.3114(V)	
	Aspect Ratio	16:9	
	Dynamic Refresh Rate technology	Adaptive-Sync	
	Dynamic Refresh Rate Activated Range	48~120Hz	
	HDR (High dynamic range)	HDR Ready	
	SDR Brightness (nits)	300	
	Contrast Ratio	1500:1	
	DCR (Dynamic Contrast Ratio)	100000000:1	
	Signal Frequency	47.11~144.23 KHz(H) / 48~120 Hz(V)	
	Refresh Rate	120Hz	
	Response Time (MPRT)	1ms(MPRT)	
	Response Time (GTG)	4ms	
	View Angles	178°(H)/178°(V)	
	NTSC (CIE1976 area percentage/overlap)	101%/82%	
	NTSC (CIE1931 area percentage/overlap)	81%/74%	
	sRGB (CIE1976 area percentage/overlap)	116%/99%	
	sRGB (CIE1931 area percentage/overlap)	114%/100%	
	Adobe RGB (CIE1976 area percentage/overlap)	100%/86%	
	Adobe RGB (CIE1931 area percentage/overlap)	84%/77%	
	DCI-P3 (CIE1976 area percentage/overlap)	93%/90%	
	DCI-P3 (CIE1931 area percentage/overlap)	84%/83%	
	Rec.709 (CIE1976 area percentage/overlap)	116%/99%	
	Rec.709 (CIE1931 area percentage/overlap)	114%/100%	
	Rec.2020 (CIE1976 area percentage/overlap)	68%/68%	
	Rec.2020 (CIE1931 area percentage/overlap)	60%/60%	
	Surface Treatment	Anti-glare	
	Display Colors	16.7M	
Color bit	8 bits (6 bits + FRC)		
I/O Ports	D-Sub	1	
	Headphone-out	1	
	USB 2.0 Type A	2	
	USB 2.0 Type B	1	
	Lock type	Kensington Lock	
	Speaker	2	
	HDMI	1	
	HDMI version	1.4b	
	HDMI HDCP version	1.4	
	DisplayPort	1	
	DisplayPort version	1.2a	
	DisplayPort HDCP version	1.3	
	Warranty	Warranty	36M
	Power	Power Type	Internal Power Board
Power Input		100~240V, 50/60Hz	
On-mode Power Consumption (KWh/1000h)		20 (SDR) 25 (HDR)	
Annual Energy Consumption (KWh)		65	
Standby-mode Power Consumption (W)		0.5	
Off-mode Power Consumption (W)		0.3	
Energy Efficiency Rating		E (SDR) F (HDR)	
Power Cord Type	C13		

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	612 x 227 x 429
	Product Dimension without Stand (WxDxH) (mm)	612 x 46 x 357
	Stand Dimension (WxDxH) (mm)	260 x 227 x 412
	Weight (Net kg)	6.2
	Weight Without Stand (kg)	3.5
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	83.9 x 13.1 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	85.4 x 14.6 x 47.1
	Weight (Gross kg)	8.5
Barcode Info	EAN	4711377260442