

## Be Your Window To The World



Picture and logos

### SELLING POINTS

- Schermo perfetto da 27" per la programmazione, il coding e la progettazione di siti web.
- Display certificato TÜV per garantire la protezione e la salute della vista.
- La tecnologia MSI EyesErgo con Anti-Flicker e Less Blue Light aiuta a prevenire l'affaticamento visivo.
- Frequenza di aggiornamento di 100Hz per un'esperienza visiva migliore e priva di sfarfallio.
- MSI Eye-Q Check aiuta a monitorare la salute degli occhi e ricorda di fare pause durante l'uso prolungato del monitor.
- Il supporto è progettato con funzioni ergonomiche, tra cui inclinazione, rotazione, regolazione in altezza e pivot.
- Mantieni la versatilità tra diversi dispositivi grazie alle molteplici opzioni di ingresso, come porte HDMI™, DisplayPort e D-Sub (VGA).
- Design standard con montaggio VESA.
- Due altoparlanti integrati.
- Una soluzione sostenibile per la protezione dell'ambiente.



1. 1x AC-in
2. 1x DisplayPort 1.2a
3. 1x HDMI™ 1.4b (FHD@100Hz)
4. 1x D-Sub (VGA)
5. 1x Line-in
6. 1x Headphone-out
7. 1x Kensington Lock
8. 1x 5-way Navigator



BUSINESS PRODUCTIVITY MONITOR

## PRO MP275PG

PRO MP275PG

## SPECIFICATION

|           |   |                                    |
|-----------|---|------------------------------------|
| Model     | SKU Number                                  | 9S6-3PC39M-053                     |
|           | Entity Mkt Name                             | PRO MP275PG                        |
|           | Part No                                     | 9S6-3PC39M-053                     |
|           | Color                                       | ID1/Black-Black                    |
| Display   | Screen Size                                 | 27" (68.58 cm)                     |
|           | Active Display Area (mm)                    | 597.888(H) x 336.312(V)            |
|           | Curvature                                   | Flat                               |
|           | Panel Type                                  | IPS                                |
|           | Resolution                                  | 1920x1080 (FHD)                    |
|           | Pixel pitch (mm)                            | 0.3114(H)x0.3114(V)                |
|           | Aspect Ratio                                | 16:9                               |
|           | Dynamic Refresh Rate technology             | Adaptive-Sync                      |
|           | Dynamic Refresh Rate Activated Range        | 48 ~ 100Hz                         |
|           | HDR (High dynamic range)                    | HDR Ready                          |
|           | SDR Brightness (nits)                       | 300                                |
|           | HDR Brightness (Peak nits)                  | -                                  |
|           | Contrast Ratio                              | 1300:1                             |
|           | DCR (Dynamic Contrast Ratio)                | 100000000:1                        |
|           | Signal Frequency                            | 52.7~137.58 KHz (H) / 48~100 Hz(V) |
|           | Refresh Rate                                | 100Hz                              |
|           | Response Time (MPRT)                        | 1ms(MPRT)                          |
|           | Response Time (GTG)                         | 4ms                                |
|           | View Angles                                 | 178°(H)/178°(V)                    |
|           | NTSC (CIE1976 area percentage/overlap)      | 82%,75%                            |
|           | NTSC (CIE1931 area percentage/overlap)      | 72%,70%                            |
|           | SRGB (CIE1976 area percentage/overlap)      | 95%,90%                            |
|           | SRGB (CIE1931 area percentage/overlap)      | 101%,92%                           |
| I/O Ports | Adobe RGB (CIE1976 area percentage/overlap) | 80%,78%                            |
|           | Adobe RGB (CIE1931 area percentage/overlap) | 74%,70%                            |
|           | DCI-P3 (CIE1976 area percentage/overlap)    | 74%,74%                            |
|           | DCI-P3 (CIE1931 area percentage/overlap)    | 73%,73%                            |
|           | Rec.709 (CIE1976 area percentage/overlap)   | 95%,90%                            |
|           | Rec.709 (CIE1931 area percentage/overlap)   | 101%,92%                           |
|           | Rec.2020 (CIE1976 area percentage/overlap)  | 51%,51%                            |
|           | Rec.2020 (CIE1931 area percentage/overlap)  | 53%,53%                            |
|           | Surface Treatment                           | Anti-glare                         |
|           | Display Colors                              | 16.7M                              |
|           | Color bit                                   | 8 bits (6 bits + FRC)              |
|           | D-Sub                                       | 1                                  |
| Warranty  | Line-in                                     | 1                                  |
|           | Headphone-out                               | 1                                  |
|           | Lock type                                   | Kensington Lock                    |
|           | Speaker                                     | 2x 2W                              |
|           | HDMI  | 1                                  |
|           | HDMI version                                | 1.4b                               |
|           | HDMI HDCP version                           | 1.4                                |
|           | DisplayPort                                 | 1                                  |
|           | DisplayPort version                         | 1.2a                               |
|           | DisplayPort HDCP version                    | 1.3                                |
| Power     | Warranty                                    | 24M                                |
|           | Power Type                                  | Internal Power Board               |
|           | Power Input                                 | 100~240V, 50/60Hz                  |
|           | On-mode Power Consumption (KWh/1000h)       | 21                                 |
|           | Annual Energy Consumption (KWh)             | 31                                 |
|           | Standby-mode Power Consumption (W)          | 0.5W                               |
|           | Off-mode Power Consumption (W)              | 0.3W                               |
|           | Energy Efficiency Rating                    | E                                  |
|           | Power Cord Type                             | C13                                |



BUSINESS PRODUCTIVITY MONITOR

## PRO MP275PG

PRO MP275PG

|                              |  |                       |
|------------------------------|--|-----------------------|
| In The Box                   | DisplayPort Cable                            | 0                     |
|                              | HDMI Cable                                   | 1                     |
|                              | DVI Cable                                    | 0                     |
|                              | USB Type A to Type B Cable                   | 0                     |
|                              | USB Type C to Type A Cable                   | 0                     |
|                              | USB Type C to Type C Cable                   | 0                     |
|                              | Thunderbolt Cable                            | 0                     |
|                              | VGA Cable                                    | 0                     |
|                              | 3.5mm audio Cable                            | 0                     |
|                              | 3.5mm combo audio Cable                      | 0                     |
|                              | 3.5mm Mic Cable                              | 0                     |
|                              | Power Cord                                   | 1                     |
|                              | AC Adaptor                                   | 0                     |
|                              | Quick Guide                                  | 1                     |
|                              | Warranty Card                                | 0                     |
|                              | Mouse Bungee Unit                            | 0                     |
| Design                       | Adjustment (Tilt)                            | -5° ~ 20°             |
|                              | Adjustment (Swivel)                          | -45° ~ 45°            |
|                              | Adjustment (Height)                          | 0 ~ 130 mm            |
|                              | Adjustment (Pivot)                           | -90° ~ 90°            |
|                              | VESA Mounting                                | 100x100mm             |
| Dimension & Weight (product) | Product Dimension with Stand (WxDxH) (mm)    | 612.1 x 226.9 x 561.4 |
|                              | Product Dimension without Stand (WxDxH) (mm) | 612.1 x 56.1 x 363.0  |
|                              | Stand Dimension (WxDxH) (mm)                 | 259.7 x 226.9 x 411.5 |
|                              | Weight (Net kg)                              | 6.03                  |
|                              | Weight Without Stand (kg)                    | 3.43                  |
| Dimension & Weight (box)     | Inside Carton Dimension (WxDxH) (cm)         | N/A                   |
|                              | Outer Carton Dimension (WxDxH) (cm)          | N/A                   |
|                              | Weight (Gross kg)                            | 8.95                  |
| Barcode Info                 | EAN  | 4711377219167         |