


Be Your Window To The World



Picture and logos

SELLING POINTS

- Il monitor docking offre la maggior parte delle funzioni necessarie con una sola connessione tramite cavo Type-C.
- Type-C con Power Delivery da 98W, Display e interruttore KVM
- Collegamento a cascata con DisplayPort Multi-Stream Transport
- Webcam FHD integrata con microfono digitale
- Ethernet RJ45 1Gbps integrata per una connessione cablata stabile
- Display certificato TÜV per la protezione e la salute della vista.
- Tecnologia MSI EyesErgo con Anti-Flicker per prevenire l'affaticamento e lo sforzo oculare.
- Frequenza di aggiornamento a 100 Hz per una migliore esperienza visiva con immagini prive di sfarfallio.
- MSI Eye-Q Check aiuta a effettuare un auto-controllo della vista e ricorda di fare pause durante l'uso prolungato del monitor.
- Supporto regolabile con design montabile per mini-PC, che migliora l'ergonomia e l'organizzazione dello spazio.
- Montabile standard VESA e con design per alloggiamento accessori.
- Due altoparlanti integrati.



1. DC-Jack
2. 2x HDMI™ 2.0b (WQHD@100Hz)
3. 1x DisplayPort 1.2a Input
4. 1x Type-C (DP Alt.) w/ 98W PD
5. 1x DisplayPort 1.2a Output
6. 1x USB 5Gbps Type-B
7. 1x LAN Port
8. 4x USB 5Gbps Type-A
9. Headphone-out
10. 1x Kensington Lock
11. 5-Way Navigator



PRO MP275QPDG

PRO MP275QPDG

SPECIFICATION

Model	SKU Number	9S6-3PC8CM-001
	Entity MKT Name	PRO MP275QPDG
	Part No	9S6-3PC8CM-001
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	71.04~186.3 KHz(H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	87%/81%
	NTSC (CIE1931 area percentage/overlap)	74%/72%
	sRGB (CIE1976 area percentage/overlap)	100%/95%
	sRGB (CIE1931 area percentage/overlap)	105%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	85%/84%
	Adobe RGB (CIE1931 area percentage/overlap)	77%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	79%/79%
	DCI-P3 (CIE1931 area percentage/overlap)	77%/77%
	Rec.709 (CIE1976 area percentage/overlap)	100%/95%
	Rec.709 (CIE1931 area percentage/overlap)	105%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	58%/58%
	Rec.2020 (CIE1931 area percentage/overlap)	55%/55%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	USB 3.2 Gen 1 Type A	4
	USB 3.2 Gen 1 Type B	1
	Lock type	Kensington Lock
	Speaker	2Wx 2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	38
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
	Power Cord Type	C13



PRO MP275QPDG

PRO MP275QPDG

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	1
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-45° ~ 45°
	Adjustment (Height)	0 ~ 130 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	614.0 x 233.9 x 578.9
	Product Dimension without Stand (WxDxH) (mm)	614.0 x 53.6 x 377.4
	Stand Dimension (WxDxH) (mm)	300.0 x 233.9 x 422.6
	Weight (Net kg)	7.05
	Weight Without Stand (kg)	4.38
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	83.1 x 13.3 x 46.8
	Outer Carton Dimension (WxDxH) (cm)	85 x 15 x 50
	Weight (Gross kg)	10.24
Barcode Info	EAN	4711377238182