

## PATH TO THE FUTURE

Inspired by the rigorous quality testing in the production of MSI G series, MSI G series' design is full of symbols of sturdiness and durability. Additionally, to provide quality user experience, G series has really simple installation process and a friendly user interface, and will be the best choice for entry level gamers to step into the game world.



## Selling Points

- Curved Gaming display (1500R) - The best gameplay immersion.
- WQHD High Resolution - Game titles will even look better, displaying more details due to the WQHD resolution.
- 165Hz Refresh Rate - Real smooth gaming.
- 1ms response time - Eliminate screen tearing and choppy frame rates.
- Wide Color Gamut - Game colors and details will look more realistic and refined, to push game immersion to its limits.
- AMD FreeSync - Prevent screen tearing.
- Anti-Flicker and Less Blue Light - Game even longer and prevent eye strain and fatigue.
- Frameless design - Ultimate gameplay experience.
- 178° wide view angle.
- Night Vision - See every detail clearly in the dark, helping you find and attack enemies before they notice.



Picture and logos: Pictures 모니터



1. 5-way joystick navigator
2. 1x DC Jack
3. 2x HDMI 2.0b
4. 1x Display Port 1.2a
5. 1x Earphone out
6. 1x Kensington lock



모 니 터

Optix G27CQ4

OPTIX G27CQ4

## Specification

|  |                                    |
|--|------------------------------------|
| USB 3.2 Gen 2x2 Type C                     | NA                                 |
| USB 3.2 Gen 2x2 Type A                     | NA                                 |
| USB 3.2 Gen 1 Type C                       | NA                                 |
| USB 3.2 Gen 1 Type A                       | NA                                 |
| USB 2.0 Type A                             | NA                                 |
| USB 2.0 Type C                             | NA                                 |
| Card Reader                                | NA                                 |
| Inside Carton Dimension (WxDxH) (mm)       | 696 x 168 x 473                    |
| Inside Carton Dimension (WxDxH) (inch)     | 27.4 x 6.61 x 18.62                |
| Weight (Net kg)                            | 5.4                                |
| Weight (Gross kg)                          | 6.7                                |
| Warranty                                   | 12M                                |
| AC Adaptor                                 | 1                                  |
| Power Cord                                 | 1                                  |
| Warranty Card                              | 1                                  |
| Quick Guide                                | 1                                  |
| Entity MKT Name                            | Optix G27CQ4                       |
| EAN  | 4719072669508                      |
| UPC  | 824142195550                       |
| UCC14                                      | 10824142195557                     |
| Thunderbolt                                | N/A                                |
| Local Dimming                              | N/A                                |
| Screen Size                                | 27" (69 cm)                        |
| Active Display Area (mm)                   | 596.736(H) x 335.664(V)            |
| Curvature                                  | Curve 1500R                        |
| Panel Type                                 | VA                                 |
| Resolution                                 | 2560x1440 (WQHD)                   |
| Pixel pitch                                | 0.2331(H)x0.2331(V)                |
| Aspect Ratio                               | 16:9                               |
| Dynamic Refresh Rate technology            | FreeSync                           |
| Activated Range                            | 48Hz-165Hz                         |
| HDR (High dynamic range)                   | N/A                                |
| SDR Brightness (nits)                      | 250                                |
| Contrast Ratio                             | 3000:1                             |
| DCR (Dynamic Contrast Ratio)               | 100000000:1                        |
| Signal Frequency                           | 70.56~214.56 KHz(H) / 48~165 Hz(V) |
| Refresh Rate                               | 165HZ                              |
| Response Time (MPRT)                       | 1ms(MPRT)                          |
| Response Time (GTG)                        | 4ms                                |
| Response Time (Tr + Tf)                    | N/A                                |
| View Angles                                | 178°(H)/178°(V)                    |
| NTSC (CIE1976 area percentageoverlap)      | 100.6% / 86.0%                     |
| NTSC (CIE1931 area percentageoverlap)      | 85.1% / 79.5%                      |
| sRGB (CIE1976 area percentageoverlap)      | 115.4% / 98.7%                     |
| sRGB (CIE1931 area percentageoverlap)      | 120.1% / 99.7%                     |
| Adobe RGB (CIE1976 area percentageoverlap) | 98.9% / 89.9%                      |
| Adobe RGB (CIE1931 area percentageoverlap) | 89.0% / 83.2%                      |
| DCI-P3 (CIE1976 area percentageoverlap)    | 91.9% / 91.8%                      |
| DCI-P3 (CIE1931 area percentageoverlap)    | 89.0% / 83.2%                      |
| Rec.709 (CIE1976 area percentageoverlap)   | 115.4% / 98.7%                     |
| Rec.709 (CIE1931 area percentageoverlap)   | 120.1% / 99.7%                     |
| Surface Treatment                          | Anti-glare                         |
| Display Colors                             | 16.7M                              |
| Color bit                                  | 8 bits                             |
| Note_DP                                    | 2560 x1440 (Up to 165Hz)           |
| Note_HDMI                                  | 2560x1440 (Up to 144Hz)            |
| Note_DVI                                   | N/A                                |
| HDMI                                       | 2                                  |
| HDMI version                               | 2.0                                |
| HDMI HDCP version                          | N/A                                |
| DisplayPort                                | 1                                  |
| DisplayPort version                        | 1.2                                |
| DisplayPort HDCP version                   | N/A                                |



모 니 터

## Optix G27CQ4

OPTIX G27CQ4

|  |   |
|--|---|
| Thunderbolt version                            | N/A   |
| Thunderbolt HDCP version                       | N/A   |
| USB Type C (DisplayPort Alternate)             | NA  |
| DVI  | NA  |
| D-Sub  | NA  |
| Mic-in   | NA  |
| Headphone-out                                  | 1   |
| Audio Combo                                    | NA  |
| USB 2.0 Type B                                 | NA  |
| USB 3.2 Gen 1 Type B                           | NA  |
| Lock type                                      | Kensington Lock   |
| Power Type                                     | External Adaptor 20V 3.25A  |
| Power Input                                    | 100~240V, 50/60Hz   |
| Adapter's KC safety Number                     | N/A   |
| Power Cord Type                                | C5  |
| QC Output                                      | NA  |
| QC Output Power                                | NA  |
| PD Output                                      | NA  |
| PD Output Power                                | NA  |
| Adjustment (Tilt)                              | -5° ~ 20°   |
| Adjustment (Swivel)                            | NA  |
| Adjustment (Height)                            | NA  |
| Adjustment (Pivot)                             | NA  |
| VESA Mounting                                  | 100x100mm   |
| Frameless Design                               | Yes   |
| Outer Carton Dimension (WxDxH) (mm)            | 711 x 183 x 498   |
| Outer Carton Dimension (WxDxH) (inch)          | 27.99 x 7.2 x 19.61   |
| Product Dimension with Stand (WxDxH) (mm)      | 611.5 x 225.4 x 457.9   |
| Product Dimension with Stand (WxDxH) (inch)    | 24.07 x 8.87 x 18.03  |
| Product Dimension without Stand (WxDxH) (mm)   | 611.5 x 75.9 x 372.8  |
| Product Dimension without Stand (WxDxH) (inch) | 24.07 x 2.99 x 14.68  |
| Stand Dimension (WxDxH) (mm)                   | 611.5 x 225.4 x 457.9   |
| Stand Dimension (WxDxH) (inch)                 | 24.07 x 8.87 x 18.03  |
| Weight (Net lbs)                               | 11.9  |
| Weight (Gross lbs)                             | 14.77   |
| Feature  | Gaming Mode<br>CrossHair<br>Adaptive Sync (Freesync)<br>5 Ways Joystick Navigator Control<br>Frameless design                                   |
| Certification                                  | 全球(WW)/CB<br>EU(歐洲)/CE-LVD<br>DE(德國)/CE-EMC<br>NALA(美國)/FCC DOC<br>TW(台灣)/BSMI<br>AU(澳大利亞)/RCM/MEPS<br>JP(日本)/PSE,VCCI<br>KR(韓國)/KC,MSIP,K-MEPS |
| DisplayPort Cable                              | 1   |
| HDMI Cable                                     | 1   |
| DVI Cable                                      | 0   |
| USB Type A to Type B Cable                     | 0   |
| USB Type C to Type A Cable                     | N/A   |
| USB Type C to Type C Cable                     | 0   |
| Thunderbolt Cable                              | N/A   |
| VGA Cable                                      | 0   |
| 3.5mm audio Cable                              | 0   |
| 3.5mm combo audio Cable                        | 0   |