

All About Gaming



Picture and logos

SELLING POINTS

- Frecuencia de actualización de 144Hz - Responde más rápido con fotogramas más fluidos.
- Tiempo de respuesta de 1ms MPRT - Elimina el desgarro de la pantalla y las tasas de fotogramas entrecortadas.
- Amplia gama de colores - Los colores y detalles del juego se verán más realistas y refinados.
- Adaptive-Sync - Evita el desgarro o tartamudeo de la pantalla, produciendo una jugabilidad ultra fluida y sin retrasos.
- Night Vision - Un sintonizador de negros inteligente para iluminar tu día al resaltar los detalles sutiles en las áreas oscuras.
- Diseño sin marco - Disfruta de la experiencia de juego definitiva con biseles súper estrechos.
- Anti-Flicker y Less Blue Light - Juega por más tiempo y previene la fatiga y el cansancio visual.
- Ángulo de visión amplio de 178° - Los colores y detalles se mantendrán nítidos en más ángulos con un ángulo de visión amplio de 178°.



1. 5-Way Navigator
- 2.AC-in
- 3.Headphone-out
- 4.HDMI™ 1.4b (FHD@144Hz)
- 5.DisplayPort 1.2a (HBR2)
- 6.Kensington Lock

SPECIFICATION

Model	Entity MKT Name	G242L E14
	Part No	9S6-3BC61T-017
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04 (H) x 296.46 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	54.18~135 KHz(H) /48~144 Hz(V)
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	97%/78%
	NTSC (CIE1931 area percentage/overlap)	75%/70%
	sRGB (CIE1976 area percentage/overlap)	111%/96%
	sRGB (CIE1931 area percentage/overlap)	106%/96%
	Adobe RGB (CIE1976 area percentage/overlap)	95%/83%
	Adobe RGB (CIE1931 area percentage/overlap)	79%/74%
	DCI-P3 (CIE1976 area percentage/overlap)	88%/83%
	DCI-P3 (CIE1931 area percentage/overlap)	78%/77%
	Rec.709 (CIE1976 area percentage/overlap)	111%/96%
	Rec.709 (CIE1931 area percentage/overlap)	106%/96%
	Rec.2020 (CIE1976 area percentage/overlap)	64%/63%
	Rec.2020 (CIE1931 area percentage/overlap)	56%/56%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18 (SDR) 22 (HDR)
	Annual Energy Consumption (KWh)	55
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) F (HDR)
Power Cord Type	C13	

Accessories	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	540.1 x 220.1 x 407
	Product Dimension without Stand (WxDxH) (mm)	540.1 x 48.7 x 316.4
	Stand Dimension (WxDxH) (mm)	318 x 220.1 x 140
	Weight (Net kg)	3.1
	Weight Without Stand (kg)	2.74
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	60 x 12.3 x 41
	Outer Carton Dimension (WxDxH) (cm)	61.5 x 13.8 x 43.3
	Weight (Gross kg)	4.8
Barcode Info	EAN	4711377289696