

All About Gaming

Inspirado en las rigurosas pruebas de calidad realizadas en la producción de la serie MSI Gaming, el diseño de MSI está repleto de símbolos de solidez y durabilidad. Además, para proporcionar una experiencia de usuario de calidad, la serie MSI Gaming cuenta con un proceso de instalación sencillo y una interfaz de usuario intuitiva, por lo que será la mejor opción para los jugadores principiantes que desean adentrarse en el mundo de los videojuegos.



Picture and logos

SELLING POINTS

- Tasa de Refresco de 144Hz: responde más rápido con fotogramas más fluidos.
- Tiempo de Respuesta de 1ms MPRT: elimina el screen tearing y las tasas de fotogramas entrecortadas.
- Amplia Gama de Colores: los colores y detalles del juego se verán más realistas y refinados.
- Adaptive-sync: evita el screen tearing o el stuttering, produciendo un gameplay ultrasuave y sin lag.
- Night Vision: sintonizador de negros inteligente para iluminar tu día resaltando los detalles finos en las zonas oscuras.
- Diseño sin marcos: disfruta de la experiencia de juego definitiva con biseles superestrechos.
- Anti-Flicker y Menos Luz Azul: juega durante más tiempo y evita la fatiga y el cansancio visual.
- Ángulo de Visión Amplio de 178°: los colores y detalles se mantendrán nítidos desde más ángulos con un ángulo de visión amplio de 178°.



1. 5-Way Navigator
2. DisplayPort 1.2a
3. HDMI™ 1.4b (FHD@144Hz)
4. Headphone-out
5. AC-in
6. Kensington Lock

SPECIFICATION

Model	Part No	9S6-3CF31M-005
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	TBD
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	TBD
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~144Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1500:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	TBD
	Refresh Rate	144HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	TBD/TBD
	NTSC (CIE1931 area percentage/overlap)	TBD/TBD
	sRGB (CIE1976 area percentage/overlap)	TBD/TBD
	sRGB (CIE1931 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1976 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1931 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1976 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1931 area percentage/overlap)	TBD/TBD
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Warranty	Warranty	24M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
	Power Cord Type	C13

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	TBD
	Weight Without Stand (kg)	TBD
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	68.8 x 12.8 x 44
	Outer Carton Dimension (WxDxH) (cm)	70.8 x 14.8 x 47
	Weight (Gross kg)	TBD
Barcode Info	EAN	4711377318853