

## PATH TO THE FUTURE

Presentamos el monitor para juegos esports MSI MAG 245F X24. Este monitor de última generación cuenta con una pantalla FHD de 24 pulgadas con una tasa de refresco ultrarrápida de 240 Hz y un tiempo de respuesta rápido de 0,5 ms (GtG, mín.). Con el MAG 245F X24, tendrás la ventaja competitiva necesaria para superar y derrotar a tus oponentes en las batallas de los videojuegos.



Picture and logos

## SELLING POINTS

- Panel Rapid IPS: proporciona un tiempo de respuesta de 0.5ms (GtG, Mín.), optimizando los colores y el brillo de la pantalla.
- Tasa de Refresco de 240Hz: responde más rápido con fotogramas más fluidos.
- Tiempo de Respuesta de 0.5ms (GtG, Mín.): elimina el desgarro de pantalla (screen tearing) y las tasas de fotogramas entrecortadas.
- AI Vision: la nueva tecnología AI Vision no solo puede revelar detalles en las zonas oscuras, sino que también mejora el brillo general y satura los colores.
- Menos Luz Azul: utiliza una solución de software para reducir la emisión de luz en la región azul-violeta del espectro de luz azul.



1. 5-Way Navi Key
2. AC-in
3. 2x HDMI™ 2.0b (FHD@240Hz)
4. DisplayPort 1.2a
5. Headphone-out
6. Kensington Lock

**SPECIFICATION**

Model	Part No	9S6-3BC81M-004
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04(H)x 296.46(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	TBD
	Signal Frequency	TBD
	Refresh Rate	240HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	TBD
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	TBD
	NTSC (CIE1931 area percentage/overlap)	TBD
	sRGB (CIE1976 area percentage/overlap)	TBD
	sRGB (CIE1931 area percentage/overlap)	TBD
	Adobe RGB (CIE1976 area percentage/overlap)	TBD
	Adobe RGB (CIE1931 area percentage/overlap)	TBD
	DCI-P3 (CIE1976 area percentage/overlap)	TBD
	DCI-P3 (CIE1931 area percentage/overlap)	TBD
	Rec.709 (CIE1976 area percentage/overlap)	TBD
	Rec.709 (CIE1931 area percentage/overlap)	TBD
	Rec.2020 (CIE1976 area percentage/overlap)	TBD
	Rec.2020 (CIE1931 area percentage/overlap)	TBD
Surface Treatment	Anti-glare	
Display Colors	TBD	
Color bit	10 bits (8 bits + FRC)	
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	24M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	TBD
	Weight Without Stand (kg)	TBD
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	TBD
Barcode Info	EAN	4711377363242