

PATH TO THE FUTURE

Presentamos el monitor para juegos esports MSI MAG 274CXF. Este monitor de última generación cuenta con una pantalla FHD de 27 pulgadas con una tasa de refresco ultrarrápida de 280 Hz



Picture and logos

SELLING POINTS

- Panel Rapid IPS: ofrece un tiempo de respuesta de 0.5ms (GtG, Mín.), optimizando los colores y el brillo de la pantalla.
- Tasa de Refresco de 240Hz: responde más rápido con fotogramas más fluidos.
- Tiempo de Respuesta de 0.5ms (GtG, Mín.): elimina el desgarrado de pantalla (screen tearing) y las tasas de fotogramas entrecortadas.
- AI Vision: la nueva tecnología AI Vision no solo puede revelar detalles en las zonas oscuras, sino que también mejora el brillo general y satura los colores.
- Menos Luz Azul: utiliza una solución de software para reducir la emisión de luz en la región azul-violeta del espectro de luz azul.



1. 5-way Joystick Navigator
2. AC-in
3. 2 x HDMI™ 2.0b (WQHD@144Hz)
4. Display Port 1.4a
5. Headphone out
6. AC-in
7. Kensington Lock

SPECIFICATION

Model	Part No	9S6-3CE41H-020
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	128.67~175 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	113%/88%
	NTSC (CIE1931 area percentage/overlap)	89%/80%
	sRGB (CIE1976 area percentage/overlap)	130%/99%
	sRGB (CIE1931 area percentage/overlap)	126%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	111%/93%
	Adobe RGB (CIE1931 area percentage/overlap)	93%/85%
	DCI-P3 (CIE1976 area percentage/overlap)	103%/96%
	DCI-P3 (CIE1931 area percentage/overlap)	93%/90%
	Rec.709 (CIE1976 area percentage/overlap)	130%/99%
	Rec.709 (CIE1931 area percentage/overlap)	126%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	75%/75%
	Rec.2020 (CIE1931 area percentage/overlap)	66%/66%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR3)
	DisplayPort HDCP version	2.3
Warranty	Warranty	24M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C13	

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	613.5 x 249.7 x 438.5
	Product Dimension without Stand (WxDxH) (mm)	613.5 x 62.1 x 362.5
	Stand Dimension (WxDxH) (mm)	340 x 250 x 143
	Weight (Net kg)	4.7
	Weight Without Stand (kg)	4.2
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	68.3 x 12.7 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	69.8 x 14 x 46.7
	Weight (Gross kg)	6.55
Barcode Info	EAN	4711377281652