



PORTABLE MONITOR

PRO MP165 E6

PRO MP165 E6

Work Smart. Play Hard.



Picture and logos

SELLING POINTS

- 15.6" FHD IPS Panel - Enhance your viewing experience.
- Portable Design helps bring it anywhere you want without strain or pressure with a protection bag.
- Tripod Socket design makes it more flexible to stand by you.
- 75mm VESA Mountable Design allows you to mount it on the wall or other devices.
- Extremely light weighting at only 0.78 kg (1.72 lbs).
- MSI EyesErgo technology with Anti-flicker, Less Blue Light, and Anti-glare panel to protect your eyes.
- Type-C/ HDMI™ Multi Input - allowing you to connect to any device effortlessly, such as a smartphone, camera, laptop, or PC.
- L-shaped Cables prevent cable bending, ensuring convenience and uninterrupted use.
- Ergonomic software, Display Kit, provides the most convenient tool, the proper color & display mode to you while working with it every day.
- Built-in Speakers - Allow you a great audio experience while on the move.



1. 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input)
2. 1x HDMI™ 2.0b (FHD@60Hz)
3. 1x Headphone-out
4. OSD Button
5. Power Button
6. 1/4" Standard Tripod Socket
7. VESA Mount Socket



PORTABLE MONITOR

PRO MP165 E6

PRO MP165 E6

SPECIFICATION

Model	Part No	9S6-3PE50M-006
	Color	ID1/Black-Black
Display	Screen Size	15.6" (39.62 cm)
	Active Display Area (mm)	344.16 (H)×193.59 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920×1080 (FHD)
	Pixel pitch (mm)	0.17925(H)×0.17925(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~60Hz
	HDR (High dynamic range)	TBD
	SDR Brightness (nits)	250
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	TBD
	Refresh Rate	60Hz
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	TBD/TBD
	NTSC (CIE1931 area percentage/overlap)	TBD/TBD
	sRGB (CIE1976 area percentage/overlap)	TBD/TBD
	sRGB (CIE1931 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1976 area percentage/overlap)	TBD/TBD
	Adobe RGB (CIE1931 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1976 area percentage/overlap)	TBD/TBD
	DCI-P3 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.709 (CIE1931 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1976 area percentage/overlap)	TBD/TBD
	Rec.2020 (CIE1931 area percentage/overlap)	TBD/TBD
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	USB Type C (DisplayPort Alternate)	2
	Headphone-out	1
	Lock type	Kensington Lock
	Speaker	1Wx 2
	HDMI	1
	HDMI version	2.0b
	HDMI HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	USB Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	TBD
	Off-mode Power Consumption (W)	TBD
	Energy Efficiency Rating	TBD



P O R T A B L E M O N I T O R

PRO MP165 E6

P R O M P 1 6 5 E 6

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	1
	USB Type C to Type C Cable	1
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	0
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	TBD
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	TBD x TBD x TBD
	Product Dimension without Stand (WxDxH) (mm)	TBD x TBD x TBD
	Stand Dimension (WxDxH) (mm)	TBD x TBD x TBD
	Weight (Net kg)	TBD
	Weight Without Stand (kg)	TBD
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	43.1 x 33.3 x 32.5
	Outer Carton Dimension (WxDxH) (cm)	43.1 x 33.3 x 32.5
	Weight (Gross kg)	TBD
Barcode Info	EAN	4711377318686