

## Be Your Window To The World



Picture and logos

## SELLING POINTS

- Perfect 21.5" screen size for the programming, coding & website design workspace.
- TÜV certified display ensures the protection and health of eyesight.
- MSI EyesErgo technology with Anti-Flicker technology helps prevent eye strain and fatigue.
- 100 Hz refresh rate provides a better viewing experience with flicker-free image.
- MSI Eye-Q Check helps have self-check eyes & reminds to take a rest while using the monitor for a long time.
- Maintain versatility across various devices by utilizing multiple input sources, such as HDMI™ and D-Sub(VGA) ports.
- Enjoy the cleanest environment with a convenient and removable cable management design.
- Standard VESA mountable & Accessory slot design.



1. 1x DC-in
2. 1x HDMI™ (1.4b)
3. 1x D-Sub (VGA)
4. 1x Headphone-out
5. 1x Kensington Lock
6. 1x 5-way navigator

**SPECIFICATION**

I/O Ports (Rear)	Card Reader	N/A
Power	Power Type	External Adaptor 12V 2.5A
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Dimension & Weight	Inside Carton Dimension (WxDxH) (inch)	N/A
	Weight (Net kg)	N/A
	Weight (Gross kg)	N/A
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension with Stand (WxDxH) (inch)	N/A
Weight	Weight Without Stand (kg)	N/A
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (inch)	N/A
Warranty	Warranty	36M
In The Box	3.5mm Mic Cable	0
	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	0
	AC Adaptor	1
	Warranty Card	0
Quick Guide	1	
Barcode Info	EAN	4711377180184
Display	Screen Size	21.5" (55 cm)
	Active Display Area (mm)	N/A
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	N/A
	HDR (High dynamic range)	N/A
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	N/A
	View Angles	178°(H)/178°(V)
	sRGB (CIE1976 area percentage/overlap)	N/A
	sRGB (CIE1931 area percentage/overlap)	N/A
	Adobe RGB (CIE1976 area percentage/overlap)	N/A
	Adobe RGB (CIE1931 area percentage/overlap)	N/A
	DCI-P3 (CIE1976 area percentage/overlap)	N/A
	DCI-P3 (CIE1931 area percentage/overlap)	N/A
	Rec.709 (CIE1976 area percentage/overlap)	N/A
	Rec.709 (CIE1931 area percentage/overlap)	N/A
	Rec.2020 (CIE1976 area percentage/overlap)	N/A
Rec.2020 (CIE1931 area percentage/overlap)	N/A	
Display Colors	16.7M	
Color bit	N/A	
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A



# PRO MP225

PRO MP225

Model	Part No	9S6-3PC6CM-007
	MKT Name	PRO MP225
	MKT Spec	PRO MP225
	Color	ID1/Black-Black
	Model	3PC6
	Local Dimming	N/A