

## PATH TO THE FUTURE



Picture and logos

## SELLING POINTS

- Panel VA - oferuje szybki, 1-milisekundowy czas reakcji MPRT matrycy, optymalizuje kolory i jasność ekranu.
- Częstotliwość odświeżania 240 Hz - Reaguj znacznie szybciej dzięki dużo bardziej płynnemu wyświetlaniu klatek obrazu na ekranie monitora.
- 1-milisekundowy czas reakcji MPRT matrycy - ciesz się płynnym generowaniem klatek obrazu i brakiem efektu rozmycia nawet podczas wyświetlania dynamicznych, kontrastowych scen.
- AI Vision - Nowa technologia AI Vision może nie tylko ujawnić szczegóły ukrywające się w ciemnych obszarach ekranu, ale także zwiększyć ogólną jasność i nasycenie kolorów.
- Technologia Less Blue Light - Zastosuj software'owe rozwiązanie, które zmniejszy emisję niebiesko-fioletowego światła w obszarze niebieskiego widma.



1. 5-Way Navi Key
2. AC-in
3. 2x HDMI™ 2.0b (FHD@240Hz)
4. DisplayPort 1.2a
5. Headphone-out
6. Kensington Lock

**SPECIFICATION**

Model	Part No	9S6-3BD01M-002
	Color	ID1/Black-Black
Display	Screen Size	23.6" (59.94 cm)
	Active Display Area (mm)	521.395(H) x 293.285(V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.27156(H)x0.27156(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	52.8~264 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	83%/75%
	NTSC (CIE1931 area percentage/overlap)	70%/68%
	sRGB (CIE1976 area percentage/overlap)	96%/94%
	sRGB (CIE1931 area percentage/overlap)	100%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	80%/80%
	Adobe RGB (CIE1931 area percentage/overlap)	73%/72%
	DCI-P3 (CIE1976 area percentage/overlap)	75%/75%
	DCI-P3 (CIE1931 area percentage/overlap)	72%/72%
	Rec.709 (CIE1976 area percentage/overlap)	96%/94%
	Rec.709 (CIE1931 area percentage/overlap)	100%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	53%/53%
	Rec.2020 (CIE1931 area percentage/overlap)	50%/50%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
Color bit	10 bits (8 bits + FRC)	
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13

Accessories	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	539.81 x 220.09 x 416.01
	Product Dimension without Stand (WxDxH) (mm)	539.81 x 81.18 x 321.82
	Stand Dimension (WxDxH) (mm)	318.04 x 220.09 x 139.10
	Weight (Net kg)	3.2
	Weight Without Stand (kg)	2.85
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	60 x 14 x 41.1
	Outer Carton Dimension (WxDxH) (cm)	62 x 16 x 43.9
	Weight (Gross kg)	5.02
Barcode Info	EAN	4711377395076