

PATH TO THE FUTURE

Introducing the MSI MAG 27C6F gaming monitor. This cutting-edge monitor features a 27-inch FHD display with a lightning-fast 180Hz refresh rate and a rapid 0.5ms (GtG, Min.) response time, thanks to the advanced Rapid VA panel technology. With the MAG 27C6F, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

SELLING POINTS

- Panel Rapid VA – oferuje szybki, 0,5-milisekundowy czas reakcji (GtG, min.) matrycy, optymalizuje kolory i jasność ekranu.
- Częstotliwość odświeżania 180 Hz – Reaguj znacznie szybciej dzięki znacznie bardziej płynnemu wyświetlaniu klatek obrazu na ekranie monitora.
- 0,5-milisekundowy czas reakcji (GtG, min.) matrycy – ciesz się płynnym generowaniem klatek obrazu i brakiem efektu rozmycia nawet podczas wyświetlania najbardziej dynamicznych, kontrastowych scen..
- AI Vision – nowa technologia AI Vision może nie tylko ujawnić szczegóły ukrywające się w ciemnych obszarach ekranu, ale także zwiększyć ogólną jasność i nasycenie kolorów.
- Technologia Adaptive-Sync – Płynna rozgrywka, pozbawiona zacięć i efektu rozrywania ekranu.
- Zgodność z technologią HDR – Umożliwia uzyskanie przyciągających wzrok szczegółów, dzięki regulacji kontrastu i cieni.
- Technologia Less Blue Light – Zastosuj software’owe rozwiązanie, które zmniejszy emisję niebiesko-fioletowego światła w obszarze niebieskiego widma.



1. 5-Way Joystick Navigator
2. AC-in
3. 2 x HDMI™ (2.0b)
4. DisplayPort (1.4)
5. Headphone out
6. Kensington Lock



MONITORY
MAG 27C6F
MAG 27C6F

SPECIFICATION

Model	SKU Number	9S6-3CE11M-015
	Entity MKT Name	MAG 27C6F
	Part No	9S6-3CE11M-015
	Color	ID1/Black-Black
	MKT Name	MAG 27C6F
	MKT Spec	MAG 27C6F
	Model	3CE1
I/O Ports (Rear)	Card Reader	N/A
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	N/A
	Annual Energy Consumption (KWh)	N/A
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	N/A
Design	Power Cord Type	C13
	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension&Weight	Frameless Design	Yes
	Inside Carton Dimension (WxDxH) (inch)	N/A
	Weight (Net kg)	N/A
Product Dimension with Stand (WxDxH)	Weight (Gross kg)	N/A
	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension with Stand (WxDxH) (inch)	N/A
Weight	Weight Without Stand (kg)	N/A
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (inch)	N/A
Warranty	Warranty	36M
Accessories	3.5mm Mic Cable	0
	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Mouse Bungee Unit	0
	VESA Screw	0
	Power Cord	1
	AC Adaptor	0
	Warranty Card	0
	Quick Guide	1
Barcode Info	EAN	4711377186537



MONITORY
MAG 27C6F
MAG 27C6F

Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H)x336.312(V)
	Curvature	Curve 1500R
	Panel Type	Rapid VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	HDR (High dynamic range)	HDR Ready
	Refresh Rate	180Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	1ms
	View Angles	178°(H)/178°(V)
	sRGB (CIE1976 area percentage/overlap)	93%/90%
	sRGB (CIE1931 area percentage/overlap)	99%/90%
	Adobe RGB (CIE1976 area percentage/overlap)	78%/78%
	Adobe RGB (CIE1931 area percentage/overlap)	72%/70%
	DCI-P3 (CIE1976 area percentage/overlap)	73%/73%
	DCI-P3 (CIE1931 area percentage/overlap)	72%/72%
	Rec.709 (CIE1976 area percentage/overlap)	93%/90%
	Rec.709 (CIE1931 area percentage/overlap)	99%/90%
	Rec.2020 (CIE1976 area percentage/overlap)	52%/52%
	Rec.2020 (CIE1931 area percentage/overlap)	50%/50%
	Display Colors	16.7M
	Color bit	8 bits
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~180Hz
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~160 KHz(H) / 60~144 Hz(V)
	NTSC (CIE1976 area percentage/overlap)	80%/74%
	NTSC (CIE1931 area percentage/overlap)	70%/68%
	Surface Treatment	Anti-glare
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	68.4 x 15.8 x 47.5
	Outer Carton Dimension (WxDxH) (cm)	70.4 x 17.8 x 50.8
	Weight (Gross kg)	N/A
I/O Ports	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A