


PATH TO THE FUTURE



Picture and logos

SELLING POINTS

- Panel QD-OLED – zachwycająca jakość obrazu i krótki czas reakcji.
- Wyjątkowo krótki, 0,03-milisekundowy czas reakcji GtG matrycy i 240-hercowa częstotliwość odświeżania.
- Technologia QD Premium Color – technologia ta sprawia, że współczynnik różnicy wartości koloru dla odwzorowania wyświetlanych na ekranie barw jest mniejszy od dwóch – Delta E ≤ 2.
- Niewiarygodne wizualizacje HDR – certyfikat VESA DisplayHDR True Black 400.
- Aplikacja Gaming Intelligence – Wykreuj idealne ustawienia związane z wizualizacją obrazu w swoich grach.
- MSI OLED Care 2.0 – Zmniejszone ryzyko utrwalenia się obrazu OLED / wypalania się obrazu.
- Funkcja przełącznika KVM - sterowanie wieloma urządzeniami za pomocą jednego zestawu klawiatury, myszy i monitora.
- Tryb konsoli – złącze HDMI™ 2.1 (UWQHD@240Hz) z pełną przepustowością 48 Gbit/s.
- 3-letnia gwarancja obejmująca wypalenie – w tym gwarancja obejmująca efekt utrwalenia / wypalania się obrazu OLED.



1. AC in
2. 2x HDMI™ 2.1 (UWQHD@240Hz)
3. 1 x DP 1.4a
4. 1 x USB Type-C (98W)
5. 2 x USB 2.0 Type A
6. 1 x USB Type B
7. 1 x Headphone



MONITORY

MPG 341CQPX QD-OLED

MPG 341CQPX QD-OLED

SPECIFICATION

Model	Part No	9S6-3DD04T-035
	Color	ID1/Black-Black
Display	Screen Size	34.18" (86.82 cm)
	Active Display Area (mm)	800.06(H) x 337.06(V)
	Curvature	Curve 1800R
	Panel Type	QD-OLED
	Resolution	3440x1440 (UWQHD)
	Pixel pitch (mm)	0.2315(H)x0.2315(V)
	Aspect Ratio	21:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	True Black 400
	SDR Brightness (nits)	250
	HDR Brightness (Peak nits)	1000
	Contrast Ratio	1500000:1
	Signal Frequency	30~390 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (GTG)	0.03ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	121.3%/94.2%
	NTSC (CIE1931 area percentage/overlap)	105.4%/92.3%
	sRGB (CIE1976 area percentage/overlap)	139.1%/100%
	sRGB (CIE1931 area percentage/overlap)	148.8%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	119.2%/97.8%
	Adobe RGB (CIE1931 area percentage/overlap)	110.3%/94.6%
	DCI-P3 (CIE1976 area percentage/overlap)	110.8%/99.3%
	DCI-P3 (CIE1931 area percentage/overlap)	109.7%/99.1%
	Rec.709 (CIE1976 area percentage/overlap)	139.1%/100%
	Rec.709 (CIE1931 area percentage/overlap)	148.8%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	80.7%/80.7%
	Rec.2020 (CIE1931 area percentage/overlap)	78.7%/78.7%
	Surface Treatment	Anti-Reflection
	Display Colors	1.07B
	Color bit	10 bits
I/O Ports	USB Type C (DisplayPort Alternate)	1
	Headphone-out	1
	USB 2.0 Type A	2
	USB 2.0 Type B	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.1
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	50
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	G
	Power Cord Type	C13



MONITORY

MPG 341CQPX QD-OLED

MPG 341CQPX QD-OLED

Accessories	DisplayPort Cable	1
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	1
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 100 mm
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	812 x 318 x 427
	Product Dimension without Stand (WxDxH) (mm)	812 x 130 x 361
	Stand Dimension (WxDxH) (mm)	633 x 318 x 371
	Weight (Net kg)	8.9
	Weight Without Stand (kg)	6.8
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	100 x 23.3 x 51.3
	Outer Carton Dimension (WxDxH) (cm)	101.5 x 24.8 x 53.6
	Weight (Gross kg)	12.7
Barcode Info	EAN	4711377191302