

## PATH TO THE FUTURE



Picture and logos

## SELLING POINTS

- 23,6-calowy panel LCD z podświetleniem LED (1920 x 1080 Full HD)
- 1-milisekundowy czas reakcji matrycy - Koniec z rozmytymi obrazami
- Zakrzywiony wyświetlacz 1800R - najbardziej odpowiedni promień krzywizny dla ludzkiego oka.
- Technologia True Color - 85% pokrycie przestrzeni barw NTSC, 110%
- Szeroki, 178-stopniowy kąt widzenia ekranu
- Zoptymalizowane pod kątem współpracy z kartami graficznymi firmy MSI z serii Gaming - bądź pewny, że uzyskasz najlepsze wrażenia.
- Technologia AMD FreeSync - połóż kres efektowi rozrywania ekranu.



1. 1 x Display Port
2. 1 x DVI
3. 1 x HDMI™

## SPECIFICATION

Model	SKU Number	0
	Part No	9S6-3EA01H-007
	Color	ID1/Black-Black
	Local Dimming	N/A
	MKT Name	Optix G241VC
	MKT Spec	Optix G241VC
	Model	3EA0
Display	Screen Size	23.6" (60cm)
	Active Display Area (mm)	521.3952(H) x 293.2848(V)
	Curvature	Curve 1800R
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.27156(H)x0.27156 (V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync
	Dynamic Refresh Rate Activated Range	48~75Hz
	SDR Brightness (nits)	250
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	54.2~84.3 KHz(H) / 48~75 Hz(V)
	Refresh Rate	75Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	8ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1931 area percentage/overlap)	85%
	sRGB (CIE1931 area percentage/overlap)	115%
	Adobe RGB (CIE1931 area percentage/overlap)	85%
DCI-P3 (CIE1931 area percentage/overlap)	85%	
Rec.709 (CIE1931 area percentage/overlap)	115%	
Surface Treatment	Anti-glare	
Display Colors	16.7M	
Color bit	8 bits	
I/O Ports	Thunderbolt	N/A
	Thunderbolt version	N/A
	Thunderbolt HDCP version	N/A
	USB Type C (DisplayPort Alternate)	N/A
	D-Sub	1
	USB 3.2 Gen 2x2 Type C	N/A
	USB 3.2 Gen 2x2 Type A	N/A
	Card reader	N/A
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	N/A
	DisplayPort HDCP version	N/A
I/O Ports (Front)	Thunderbolt	N/A
	USB 3.2 Gen 2x2 Type C	N/A
	USB 3.2 Gen 2x2 Type A	N/A
	Card Reader	N/A
Warranty	Warranty	36M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	21
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	N/A	

Accessories	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	N/A
	USB Type C to Type C Cable	0
	Thunderbolt Cable	N/A
	VGA Cable	N/A
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	N/A
	Design	Adjustment (Tilt)
VESA Mounting		100x100mm
Frameless Design		Yes
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	543 x 404 x 192
	Product Dimension without Stand (WxDxH) (mm)	543 x 353 x 62
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	4.1
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	60 x 16.4 x 40.9
	Outer Carton Dimension (WxDxH) (cm)	61.5 x 17.9 x 43.4
	Weight (Gross kg)	5.5
Barcode Info	EAN	4719072618971
Dimension&Weight	Inside Carton Dimension (WxDxH) (mm)	621 x 148 x 421
	Inside Carton Dimension (WxDxH) (inch)	24.45 x 5.83 x 16.57
	Weight (Net kg)	4.1
	Weight (Gross kg)	5.5
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	543 x 404 x 192
	Product Dimension with Stand (WxDxH) (inch)	21.38 x 15.91 x 7.56
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	624 x 149 x 428
	Outer Carton Dimension (WxDxH) (inch)	24.57 x 5.87 x 16.85