

PATH TO THE FUTURE



Selling Points

Modern MD241PW

Monitor z serii MSI Modern MD241PW - 23,8-calowy panel o rozdzielczości Full HD, oferuje on technologie Less Blue Light i Anti-Flicker. Wyposażony jest również w warstwę antyodblaskową i współpracuje z aplikacją Display Kit. Monitor zgodny jest ze standardem montażowym VESA, ma wbudowane głośniki i został zaprojektowany z myślą o stworzeniu eleganckiego oraz spersonalizowanego designu, który będzie idealnie pasował do każdego miejsca w Twoim domu.

- Wyświetlacz z certyfikatem TÜV, chroni wzrok i dba o zdrowie oczu
- Technologie Less Blue Light i Anti-Flicker chronią Twój wzrok przed zmęczeniem i znużeniem.
- 75-hercowa częstotliwość odświeżania oferuje znacznie lepsze wizualne wrażenia
- Zajmij wygodną dla siebie pozycję przed ekranem i skup się na lekcjach oraz zadaniach domowych
- Duża elastyczność związana z możliwością podłączenia do monitora dwóch różnych źródeł sy ...



Picture and logos: Pictures Business Productivity Monitor

1. 1x HDMI(1.4b)
2. 1x D-Sub (VGA)
3. 1x Mic-in
4. 1x Headphone-out
5. 1x Kensington Lock



Specification

USB 3.2 Gen 2x2 Type C	NA
USB 3.2 Gen 2x2 Type A	NA
USB 3.2 Gen 1 Type C	NA
USB 3.2 Gen 1 Type A	NA
USB 2.0 Type A	NA
USB 2.0 Type C	NA
Card Reader	NA
Inside Carton Dimension (WxDxH) (mm)	804 x 157 x 395
Inside Carton Dimension (WxDxH) (inch)	31.65 x 6.18 x 15.55
Weight (Net kg)	4.7
Weight (Gross kg)	6.5
Warranty	36M
AC Adaptor	1
Power Cord	1
Warranty Card	1
Quick Guide	1
EAN	4719072795689
UPC	824142241288
UCC14	10824142241285
Thunderbolt	NA
Local Dimming	NA
Screen Size	23.8" (60cm)
Active Display Area (mm)	527.04(H)*296.46(V)mm
Curvature	Flat
Panel Type	IPS
Resolution	1920x1080 (FHD)
Pixel pitch	0.2745(H)x0.2745(V)
Aspect Ratio	16:9
Dynamic Refresh Rate technology	NA
Activated Range	NA
HDR (High dynamic range)	NA
SDR Brightness (nits)	250
Contrast Ratio	1000:1
DCR (Dynamic Contrast Ratio)	100000:1
Signal Frequency	30~112 KHz(H) / 48~75 Hz(V)
Refresh Rate	75Hz
Response Time (MPRT)	NA
Response Time (GTG)	5ms



BUSINESS PRODUCTIVITY MONITOR

Modern MD241PW

MODERN MD241PW

Response Time (Tr + Tf)	14ms
View Angles	178°(H)/178°(V)
NTSC (CIE1976 area percentageoverlap)	95.98%/80.61%
NTSC (CIE1931 area percentageoverlap)	77.71%/73.10%
sRGB (CIE1976 area percentageoverlap)	110.03%/98.38%
sRGB (CIE1931 area percentageoverlap)	109.71%/98.07%
Adobe RGB (CIE1976 area percentageoverlap)	94.21%/85.65%
Adobe RGB (CIE1931 area percentageoverlap)	81.33%/75.91%
DCI-P3 (CIE1976 area percentageoverlap)	87.72%/85.19%
DCI-P3 (CIE1931 area percentageoverlap)	80.87%/80.33%
Rec.709 (CIE1976 area percentageoverlap)	NA
Rec.709 (CIE1931 area percentageoverlap)	NA
Surface Treatment	Anti-glare
Display Colors	16.7M
Color bit	8 bits
Note_DP	NA
Note_HDMI	1920 x 1080 (Up to 75Hz)
Note_DVI	N/A
HDMI	1
HDMI version	1.4
HDMI HDCP version	1.4
DisplayPort	NA
DisplayPort version	NA
DisplayPort HDCP version	NA
Thunderbolt version	NA
Thunderbolt HDCP version	NA
USB Type C (DisplayPort Alternate)	1
DVI	NA
D-Sub	NA
Mic-in	NA
Mic-in upstream	NA
Headphone-out	1
Audio Combo	NA
USB 2.0 Type B	NA
USB 3.2 Gen 1 Type B	NA
Lock type	Kensington Lock
Power Type	External Adaptor 19V 2.58A
Power Input	100~240V, 50/60Hz
Adapter's KC safety Number	NA
Power Cord Type	C13
QC Output	NA
QC Output Power	NA
PD Output	NA
PD Output Power	NA
Adjustment (Tilt)	-5° ~ 20°
Adjustment (Swivel)	-30° ~ 30°
Adjustment (Height)	0 ~ 110 mm
Adjustment (Pivot)	-90° ~ 90°
VESA Mounting	75x75mm
Frameless Design	Yes
Outer Carton Dimension (WxDxH) (mm)	814 x 167 x 417
Outer Carton Dimension (WxDxH) (inch)	32.05 x 6.57 x 16.42
Product Dimension with Stand (WxDxH) (mm)	541 x 200 x 380
Product Dimension with Stand (WxDxH) (inch)	21.3 x 7.87 x 14.96
Product Dimension without Stand (WxDxH) (mm)	541 x 48 x 322
Product Dimension without Stand (WxDxH) (inch)	21.3 x 1.89 x 12.68
Stand Dimension (WxDxH) (mm)	230 x 200 x 415
Stand Dimension (WxDxH) (inch)	9.06 x 7.87 x 16.34
Weight (Net lbs)	10.36
Weight (Gross lbs)	14.33
Feature	Frameless design
Certification	全球(WW)/CB EU(歐洲)/CE-LVD DE(德國)/CE-EMC NALA(美國)/FCC DOC



BUSINESS PRODUCTIVITY MONITOR

Modern MD241PW

MODERN MD241PW

TW(台灣)/BSMI
AU(澳大利亞)/RCM/MEPS
JP(日本)/PSE,VCCI
CCC

DisplayPort Cable	0
HDMI Cable	1
DVI Cable	0
USB Type A to Type B Cable	0
USB Type C to Type A Cable	0
USB Type C to Type C Cable	0
Thunderbolt Cable	0
VGA Cable	0
3.5mm audio Cable	0
3.5mm combo audio Cable	0