

Be Your Window To The World



Picture and logos

SELLING POINTS

- 23,8-calowy ekran idealny do programowania, kodowania i projektowania stron internetowych.
- Wyświetlacz z certyfikatem TÜV, chroni wzrok i dba o zdrowie oczu.
- Technologia MSI EyesErgo z systemem Anti-flicker, która zapobiega nadwyrężeniu oraz zmęczeniu oczu i pomaga chronić Twój wzrok.
- 100-hercowa częstotliwość odświeżania oferuje lepsze wrażenia wizualne i sprawia, że obraz pozbawiony jest efektu migotania.
- Funkcja MSI Eye-Q Check pomaga w samodzielnej kontroli wzroku i przypomina o konieczności odpoczynku podczas długotrwałego korzystania z monitora.
- Podstawa monitora charakteryzuje się szeregiem ergonomicznych funkcji, w tym regulacją nachylenia, obrotem, i możliwością obrotu ekranu o 90° (pivot).
- Ciesz się wszechstronną współpracą z różnymi urządzeniami, korzystając z wielu wejściowych źródeł sygnału, takich jak port HDMI™, DisplayPort i złącze D-Sub (VGA).
- Zgodność ze standardem montażowym VESA.
- Dwa wbudowane głośniki.
- Zrównoważone rozwiązanie chroniące środowisko.



1. 1x AC-in
2. 1x DisplayPort (1.2a)
3. 1x HDMI™ 1.4b (FHD@100Hz)
4. 1x D-Sub (VGA)
5. 1x Line-in
6. 1x Headphone-out
7. 1x Kensington Lock
8. 1x 5-way navigator

SPECIFICATION

Model	Part No	9S6-3PC1CM-004
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60cm)
	Active Display Area (mm)	527(H) x 296 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48 ~ 100Hz
	HDR (High dynamic range)	N/A
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	52.416~112.5 KHz(H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	89/84
	NTSC (CIE1931 area percentage/overlap)	77/75
	sRGB (CIE1976 area percentage/overlap)	102/94
	sRGB (CIE1931 area percentage/overlap)	108/98
	Adobe RGB (CIE1976 area percentage/overlap)	87/84
	Adobe RGB (CIE1931 area percentage/overlap)	80/77
	DCI-P3 (CIE1976 area percentage/overlap)	81/80
	DCI-P3 (CIE1931 area percentage/overlap)	80/80
	Rec.709 (CIE1976 area percentage/overlap)	102/94
	Rec.709 (CIE1931 area percentage/overlap)	108/98
	Rec.2020 (CIE1976 area percentage/overlap)	59/59
	Rec.2020 (CIE1931 area percentage/overlap)	57/57
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
I/O Ports	D-Sub	1
	Line-in	1
	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2
	DisplayPort HDCP version	1.3
	Warranty	Warranty
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	18
	Annual Energy Consumption (KWh)	N/A
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
Power Cord Type	C13	



MONITORY Z SERII BUSINESS
PRODUCTIVITY

PRO MP245G

PRO MP245G

Accessories	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	N/A
	Product Dimension without Stand (WxDxH) (mm)	N/A
	Stand Dimension (WxDxH) (mm)	N/A
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	60 x 12.5 x 40
	Outer Carton Dimension (WxDxH) (cm)	61.8 x 14.3 x 43
	Weight (Gross kg)	N/A
Barcode Info	EAN	4711377211079