

## Business & Productivity Monitor



Picture and logos

### SELLING POINTS

- Ciesz się perfekcyjną jakością przeglądania stron internetowych dzięki wysokiej, 100-hercowej częstotliwości odświeżania ekranu.
- Poszerzony, 24,5-calowy wyświetlacz — ciesz się ulepszonym ekranem w ograniczonej przestrzeni.
- Najlepszy rozmiar ekranu do biura i na biurko, który zgodny jest ze strefą wzrokowego komfortu.
- Wyświetlacz z certyfikatem TÜV, chroni wzrok i dba o zdrowie Twoich oczu.
- Technologia MSI EyesErgo z systemem Anti-flicker zapobiega nadwyrężeniu i zmęczeniu oczu oraz pomaga chronić Twój wzrok.
- Funkcja MSI Eye-Q Check pomaga w samodzielnej kontroli wzroku i przypomina o konieczności odpoczynku podczas długotrwałego korzystania z monitora.
- Ciesz się wszechstronną współpracą z różnymi urządzeniami, dzięki możliwości skorzystania z wielu źródeł sygnału wejściowego, takich jak porty HDMI™ i złącza DisplayPort.
- Ciesz się porządkiem na biurku dzięki wygodnemu, zdejmowanemu i umieszczonemu na tylnej stronie stopki monitora uchwytowi do prowadzenia kabli.
- Technologia HDR pozwala uzyskać obrazy o większej szczegółowości.



1. 5-way Navigator
2. 1x DC Jack
3. 1x Headphone-out
4. 1x DisplayPort 1.2a
5. 1x HDMI™ 1.4b (FHD@100Hz)
6. Kensington Lock

**SPECIFICATION**

Model	Part No	9S6-3PD7CT-013
	Color	ID1/Black-Black
Display	Screen Size	24.5" (62.23cm)
	Active Display Area (mm)	543.744(H) x 302.616(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2832(H)x0.2802(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~100Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	250
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	40.08~112.5 KHz(H) / 48~100 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	87%/79%
	NTSC (CIE1931 area percentage/overlap)	73%/70%
	sRGB (CIE1976 area percentage/overlap)	100%/97%
	sRGB (CIE1931 area percentage/overlap)	103%/96%
	Adobe RGB (CIE1976 area percentage/overlap)	86%/85%
	Adobe RGB (CIE1931 area percentage/overlap)	76%/74%
	DCI-P3 (CIE1976 area percentage/overlap)	80%/80%
	DCI-P3 (CIE1931 area percentage/overlap)	76%/76%
	Rec.709 (CIE1976 area percentage/overlap)	100%/97%
	Rec.709 (CIE1931 area percentage/overlap)	103%/96%
	Rec.2020 (CIE1976 area percentage/overlap)	58%/58%
	Rec.2020 (CIE1931 area percentage/overlap)	54%/54%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
Color bit	8 bits (6 bits + FRC)	
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	1.4b
	HDMI HDCP version	1.4
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	1.3
Warranty	Warranty	24M
Power	Power Type	External Adaptor 12V 2A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	14 (SDR) 30 (HDR)
	Annual Energy Consumption (KWh)	27
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	D

Accessories	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	0
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-3.5° ~ 21.5°
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	560 x 174 x 397
	Product Dimension without Stand (WxDxH) (mm)	560 x 28 x 328
	Stand Dimension (WxDxH) (mm)	174 x 174 x 111
	Weight (Net kg)	1.9
	Weight Without Stand (kg)	1.7
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	62.5 x 11.5 x 41
	Outer Carton Dimension (WxDxH) (cm)	64 x 13 x 43.3
	Weight (Gross kg)	4.
Barcode Info	EAN	4711377259057